

ARMY RESEARCH LABORATORY



# The Role of Transverse Flow in Co-Injection Resin Transfer Molding

by Bruce K. Fink, Emanuele F. Gillio,  
Suresh G. Advani, and John W. Gillespie Jr.

ARL-TR-2135

December 1999

Approved for public release; distribution is unlimited.

20000118 053

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

# Army Research Laboratory

Aberdeen Proving Ground, MD 21005-5069

---

---

ARL-TR-2135

December 1999

## The Role of Transverse Flow in Co-Injection Resin Transfer Molding

Bruce K. Fink

Weapons and Materials Research Directorate

Emanuele F. Gillio, Suresh G. Advani, and John W. Gillespie Jr.

University of Delaware

---

---

## Abstract

---

A co-injection resin transfer molding (CIRTM) process has been developed at the U.S. Army Research Laboratory (ARL) in collaboration with the University of Delaware. It enables two or more resins to be simultaneously injected into a mold filled with a stationary fiber preform. This process allows for the manufacturing of cocured multilayer multiresin structures in a single processing step. A separation layer is used to provide resin compatibility during cure and to control resin mixing. In this study, scaling issues relating the role of transverse permeability in resin mixing are investigated. This report presents two different approaches taken to understand the causes of transverse flow and to quantify the amount of transverse flow. The first approach is a one-dimensional (1-D) model, which explains the important parameters that govern the flow in CIRTM. The second approach is based on an existing finite element code, which is modified to allow for the injection of multiple resins. The total amount of transverse flow was quantified using the finite element code. This research shows that the CIRTM process requires a totally impermeable separation layer if CIRTM is used to manufacture large parts and/or if the resins injected have significantly different viscosities.

## Acknowledgments

The authors would like to thank Murat Sozer for his help in developing the flow modeling input script.

INTENTIONALLY LEFT BLANK.

# Table of Contents

	<u>Page</u>
Acknowledgments.....	iii
List of Figures.....	vii
1. Background and Motivation .....	1
2. One-Dimensional (1-D) Model .....	2
3. Finite Element Model.....	7
4. Transverse Permeability.....	9
5. Part Length Considerations .....	11
6. Conclusions .....	12
7. References .....	15
Distribution List .....	17
Report Documentation Page .....	27

INTENTIONALLY LEFT BLANK.


## List of Figures

<u>Figure</u>		<u>Page</u>
1.	Cross Section of Integral Armor .....	1
2.	Schematic of the 1-D Flow Model in CIRTM .....	2
3.	Effect of the Transverse Permeability on Distance Between Flow Fronts in Top and Bottom Layers .....	6
4.	Total Transverse Flow as Percentage of Half of Mold Volume for Different Values of Transverse Permeability .....	7
5.	Schematic of Finite Element Mesh Used to Model Co-Injection Process .....	9
6.	Total Transverse Flow for Different Transverse Permeabilities .....	10
7.	Percentage of Cross Flow With Respect to Half the Mold Volume as a Function of the Ratio of In-Plane to Transverse Permeability .....	11
8.	Effect of Part Length on Total Percentage of Transverse Flow .....	12
9.	Percentage of Transverse Flow as a Function of Part Length.....	13

INTENTIONALLY LEFT BLANK.

# 1. Background and Motivation

Several composites application require multiple layers each serving a specific task while being integrated together in a single structure. For example, lightweight composite armor (Figure 1) incorporates different layers of different materials, which serve as ballistic protection, structural reinforcements, fire smoke and toxicity barriers, and signature management, while being integrated together into a single structure. Currently, the manufacturing of these kind of multilayer structures takes place in multiple steps in which each layer is manufactured individually and then bonded to the others. This process is not cost effective, and the secondary bonding procedures can introduce a number of defects into the final part. Pike, McArthur, and Schade [1] have shown that vacuum-assisted resin transfer molding (VARTM) processes can introduce significant cost savings, but they have been limited to a single resin system.



**Figure 1. Cross Section of Integral Armor.**

Co-injection resin transfer molding (CIRTM) is a new process developed by the U.S. Army Research Laboratory (ARL) and the University of Delaware that enables the manufacturing of multilayer hybrid structures in a single processing step [2]. CIRTM takes advantage of the unique properties and the cost effectiveness of existing liquid molding processes and improves

them by reducing the number of steps necessary to manufacture multilayer structures. Gillio [3] and Gillio et al. [4] give a complete overview of the co-injection process.

The applications of this process are not limited to integral armor. A number of applications exist for multilayer structures in which a thick structural layer of vinyl ester or polyester is combined with a thin layer of phenolic resin for fire, smoke, and toxicity protection. These applications include navy ship decks, containers to transport goods, rail cars, and anywhere composites want to be applied where flammability of materials is of concern.

## 2. One-Dimensional (1-D) Model

A simplified schematic of the co-injection setup is shown in Figure 2. In the majority of cases, the flow of a polymer inside a mold filled with a stationary fiber bed is modeled using Darcy's law [5]. The macroscopic velocity,  $u$ , is given by

$$u = \frac{\kappa}{\mu} \frac{dP}{dx}, \quad (1)$$

where  $\kappa$  is the permeability of the fiber preform, and  $\mu$  is the viscosity of the resin. In co-injection, the top and the bottom preforms can have different permeabilities and the resins injected can have different viscosities leading to different resin velocities between the top and the bottom halves of the mold. The injection is assumed to be at constant pressure since this is the case in the majority of VARTM processes.




Figure 2. Schematic of 1-D Flow Model in CIRTM.

In such a case, the velocities of the two flow fronts is given by

$$u_1 = \frac{\kappa_1 P_i}{\mu_1 l_1} \quad (2)$$

and

$$u_2 = \frac{\kappa_2 P_i}{\mu_2 l_2}. \quad (3)$$

It follows that, if the ratios of permeability to viscosity are the same in both layers, the flow velocities will be the same. In most applications, this is not the case and one of the flow fronts will move ahead of the other.

As the flow moves through the mold, a pressure profile develops in both the top and the bottom halves of the mold. In the case where the cross flow between the two layers is small, these pressure profiles can be assumed to be linear. In this model, both pressure profiles are assumed to be linear. If the ratio of permeability to viscosity is different between the two layers,  $l_1$  and  $l_2$  will be different and a pressure gradient will form between the top and the bottom halves of the mold. This pressure gradient will drive the transverse flow. The transverse flow will be given by

$$u_3 = \frac{2\kappa_3 P'}{\mu_1 (h_1 + h_2)}, \quad (4)$$

where  $\kappa_3$  is the transverse permeability of the middle layer,  $(h_1 + h_2)/2$  is the distance between the midpoints of the two layers, and  $P'$  is the average pressure difference between the two layers. Since both pressure profiles are assumed to be linear, and recalling that the pressure is zero in front of the fluid front (i.e., where the preform is not impregnated),  $P'$  is given by

$$P' = \frac{P_i (l_1 - l_2)}{l_1 2}. \quad (5)$$

Here, the assumption has been made that the ratio of permeability to viscosity of layer one is greater than that of layer two. Substituting equation (5) into equation (4), an equation for the cross flow is obtained as a function of the inlet pressure and the position of the flow fronts:

$$u_3 = \frac{\kappa_3 P_i (l_1 - l_2)}{\mu_1 l_1 (h_1 + h_2)} \quad (6)$$

In equation (4) and (6), the viscosity of fluid one was used, assuming that the ratio of permeability to viscosity of layer one is greater than that of layer two, which is the case in Figure 2. Equation (6) can be verified in the extreme cases: if the transverse permeability is zero, the transverse flow is zero; if the two flow fronts are at the same location (i.e.,  $l_1 = l_2$ ), there is no pressure gradient and the transverse flow is zero. A mass balance yields

$$Q_1 - Q_T = Q_2 + Q_T, \quad (7)$$

where  $Q_1$  and  $Q_2$  are the flow rates through injection gates one and two, respectively, and  $Q_T$  is the flow rate through the separation layer. Assuming unit width of the part, the flow rates are given by

$$Q_1 = \frac{\kappa_1 P_i}{\mu_1 l_1} h_1, \quad (8)$$

$$Q_2 = \frac{\kappa_2 P_i}{\mu_2 l_2} h_2, \quad (9)$$

and

$$Q_T = \frac{\kappa_3 P_i (l_1 - l_2)^2}{\mu_1 l_1 (h_1 + h_2)}. \quad (10)$$

Knowing the flow rates, it is possible to compute the flow progression in the x direction based on a given time step,  $dt$ . The positions of the two flow fronts can be obtained using the following expressions:

$$l_1 = l_1 + \frac{(Q_1 - Q_T) \cdot dt}{h_1 \cdot V_{f1}}, \quad (11)$$

and

$$l_2 = l_2 + \frac{(Q_2 + Q_T) \cdot dt}{h_2 \cdot V_{f2}}, \quad (12)$$

where  $V_{f1}$  and  $V_{f2}$  are the respective fiber volume fractions of each preform.


Clearly, from equations (2) and (3), the flow in the layer with the highest ratio of permeability to viscosity will be ahead. However, the distance between flow fronts will not increase continuously but, rather, it will slowly approach a steady-state scenario. The exact time, or position, at which this occurs depends on the total amount of transverse flow, which depends on a number of other factors such as the transverse permeability and the pressure gradient formed in the transverse direction. Figure 3 shows a plot of the distance between flow fronts vs. the flow front positions for a variety of different transverse permeabilities. All of the cases eventually reach steady state. It should be noted that the nondimensional ratio  $R$  was used in Figure 3 because it emphasizes the various parameters that affect the resin flow. However, in this graph, only the transverse permeability was changed.

This behavior can also be observed in the equations. Substituting equations (8), (9), and (10) into equation (7) and assuming the two layers have the same thickness,  $h$ , and the fluids the same viscosity, the distance between the two flow fronts, normalized by the thickness, is given by

$$\frac{l_1 - l_2}{h} = -\frac{\kappa_2 h}{2l_2 \kappa_3} + \frac{1}{2} \sqrt{\left(\frac{\kappa_2 h}{l_2 \kappa_3}\right)^2 + 4 \frac{\kappa_1 - \kappa_2}{\kappa_3}}. \quad (13)$$

If the permeabilities of the two preforms are the same, the distance between the two flow fronts reduces to zero, as would be expected. Additionally, as  $l_2$  becomes large, the distance between the two flow fronts becomes constant. Taking the limit of equation (13) as  $l_2$  approaches infinity yields


$$\frac{l_1 - l_2}{h} = \sqrt{\frac{\kappa_1 - \kappa_2}{\kappa_3}}. \quad (14)$$



**Figure 3. Effect of Transverse Permeability on Distance Between Flow Fronts in Top and Bottom Layers. All Variables Are Normalized With Respect to the Thickness of One Layer.**

This equation was originally introduced by Brusckhe [6].

The term under the square root on the right-hand side of equation (14) is exactly the same as the ratio  $R$  that was used in Figure 3, except that the viscosities were assumed to be the same and therefore they canceled out. The second important result that can be obtained from a simple 1-D model is the total amount of transverse flow. Figure 4 shows the effect of transverse permeability on the total amount of transverse flow. In this case, the permeabilities of the two layers were assumed to be the same, while the viscosity of one resin was four times that of the other. Under these conditions, different transverse permeabilities were used in an attempt to control the transverse flow. The trend observed is that the transverse flow increases rapidly in the initial stages of mold filling and, subsequently, when the distance between the flow fronts becomes constant, the total transverse flow does not increase significantly.



**Figure 4. Total Transverse Flow as Percentage of Half of Mold Volume for Different Values of Transverse Permeability. The Flow Front Position Is Normalized With Respect to the Thickness of the Layer.**


### 3. Finite Element Model

Liquid Injection Molding Simulation (LIMS) is a finite element code developed at the University of Delaware [7-12]. It is a two-dimensional (2-D) flow modeling package that can deal with complex geometries and multiple injection gates and vent locations. In traditional VARTM processes, the thickness is much smaller than the other two dimensions. The flow in the thickness direction can therefore be neglected, and a 2-D model can be used. However, this is not the case in CIRTM because the flow in the thickness direction plays an important role in determining the amount of mixing that takes place between the two resins.

In LIMS, the user creates the geometry of the part using a commercial finite element code. Once the geometry is created, it is converted into a file that is readable for LIMS. The user must then enter all of the material properties (i.e., resin viscosity, preform permeability, etc.) and the processing parameters (i.e., injection gates location, inlet pressure or flow rates, etc.). LIMS can then process all of this information and reproduce the pressure field in the mold, the filling history, etc. To simulate the co-injection process, the program was slightly modified. Only one type of resin can be injected into the mold using LIMS, but multiple injection gates are possible. Since the flow patterns are governed by the ratios of viscosity to permeability, the permeabilities in the top and the bottom layers were modified to account for the injection of resins with different viscosities.

The geometry used is shown in Figure 5, where the flow was modeled in the one and the three direction to be able to account for the transverse flow. LIMS is based on a control volume finite element approach [7]. It associates a control volume with every node in the finite element mesh (Figure 5) and, as the flow front moves, it assigns a fill factor to each node. If the control volume of a specific node is empty, the fill factor will be zero; if it is completely full, the fill factor will be one; and if it is partially full, the fill factor will reflect the percentage of the control volume that is filled. A script was written that calculates the volume of every node; it then uses the fill factors at each time step to determine how much fluid has entered the bottom half and the top half of the mold (Figure 5). These values are then compared to the amount of fluid injected through the two injection gates. The difference between fluid injected in one layer and volume filled in the same layer is computed, and this will be the transverse flow for this time step from mass conservation. Additionally, at every time step, the script compares the total fluid injected through both gates to the total volume filled in the two halves of the mold; the ratio of these two values should be one at every step. Finally, the accuracy of the results was checked by mesh refinement.

A parametric study was conducted on two parameters that the 1-D model had shown to be fundamental to understanding the transverse flow. These parameters were the transverse permeability of the separation layer and the total length of the part. The 1-D model emphasized




**Figure 5. Schematic of Finite Element Mesh Used to Model Co-Injection Process.**

other parameters, particularly the difference between the ratio of permeability to viscosity of the two layers. However, these values were maintained the same because, in a real world application, once the materials are selected, their properties vary only slightly.


#### **4. Transverse Permeability**

To better understand the role and importance of this parameter, a parametric study was conducted. The minimum transverse permeability was selected so that the total transverse flow would be less than 1% of half of the mold volume. The maximum transverse permeability was selected to be one order of magnitude greater than the in plane permeability. Figure 6 shows a comparison between the different transverse flows obtained. As expected, the transverse flow increases with decreasing transverse permeability (i.e., increasing R ratio). As before, the R ratio was used to emphasize all parameters that can effect the transverse flow. However,



**Figure 6. Total Transverse Flow for Different Transverse Permeabilities. Transverse Flow Is Normalized With Respect to Half of the Mold Volume. Time Is Normalized With Respect to Total Filling Time.**

permeabilities and viscosities of the two layers were maintained constant. Additionally, the filling time decreases with increasing transverse flow. This happens because the maximum fill time is the time it would take the higher viscosity resin to fill its half of the mold without any cross flow. The transverse flow can be thought of as an additional inlet, so, as the transverse flow increases, it will take less time to fill the mold. One final behavior that should be observed is that the total transverse flow does not increase linearly with decreasing permeability. Figure 7 shows the total transverse flow as a function of transverse permeability. The transverse flow increases rapidly when the transverse permeability decreases from 6 orders of magnitude greater than the in plane permeability to 4 orders of magnitude. After this point, it slowly levels off.




**Figure 7. Percentage of Cross Flow With Respect to Half the Mold Volume as a Function of the Ratio of In-Plane to Transverse Permeability.**

The results from this parametric study show that it is extremely difficult to control the transverse flow. The only case in which it was possible to limit the transverse flow to less than 1% was by using an extremely small transverse permeability. In practice, it is very difficult to find a separation layer with a transverse permeability that is approximately 7 orders of magnitude smaller than the in-plane permeability of a reinforcing preform. Consequently, this parametric study supports our experimental work showing that an impermeable layer is required.

## 5. Part Length Considerations

The 1-D model also emphasized the effect of the part length on the transverse flow. Figure 4 showed that the amount of transverse flow eventually levels off, but this only happens after considerably long distances. The parametric study was conducted by varying the length of the part while maintaining all other parameters constant. Figure 8 shows the total transverse flow as a function of time. Time has been normalized with respect to the total fill time of each mold.




**Figure 8. Effect of Part Length on Total Percentage of Transverse Flow. Transverse Flow Is Normalized With Respect to Half the Mold Size. Time Is Normalized With Respect to Total Filling Time.**

The percentage cross flow is computed with respect to half of the mold volume. Clearly, the amount of cross flow increases with increasing mold size. This is also reflected in Figure 9, which suggests that the transverse flow does not increase linearly but, rather, eventually levels off. This behavior is expected because it was also observed in the 1-D model.

## 6. Conclusions

The goal of understanding the parameters that govern the flow in CIRTM was met using the 1-D model. In CIRTM, as the resins fill the two layers in the mold, two pressure profiles develop. These profiles are determined by the ratio of the permeability of the preform to the viscosity of the resin. Since, in the majority of cases the two ratios are different, two different pressure profiles develop in the top and bottom layer. When this occurs, a pressure gradient



**Figure 9. Percentage of Transverse Flow as a Function of Part Length. Log Curve Fit Is Shown.**

forms in the transverse direction and drives the transverse flow. The model also showed that the amount of transverse flow increases rapidly until it reaches a steady-state point. All of the results from this model qualitatively matched the ones from the finite element model.

The finite element model allowed measuring the amount of transverse flow and determining the importance of the transverse permeability and the effect of part length on the transverse flow. The model also relaxed the assumption of linear pressure profile in each half of the mold. It showed that a transverse permeability 7 orders of magnitude smaller than the in-plane permeability is needed to reduce the transverse flow to less than 1% of half the mold size. In practice, it is almost impossible to find a preform material with this property. Additionally, the finite element code proved that increasing the part length and, therefore, the distance that the resin must travel, increases the amount of transverse flow. As in the 1-D model, the amount of transverse flow seems to eventually reach a steady-state situation but only after a significant amount of mixing has occurred.

Overall, the results from the two models agree qualitatively and also agree with preliminary experiments conducted in the lab. In order to use the co-injection process for large structures, it is necessary to use a completely impermeable separation layer. This will completely eliminate transverse flow. For smaller scale applications, the results presented in this study provide useful guidance for selection of resin and preforms to minimize transverse flow.

## 7. References

1. Pike, T., M. McArthur, and D. Schade. "Vacuum Assisted Resin Transfer Molding of a Layered Structural Laminate for Application on Ground Combat Vehicles." *Proceedings of the 28th International SAMPE Technical Conference*, pp. 374-380, Seattle, WA, 4-7 November 1996.
2. Fink, B. K., J. W. Gillespie, Jr., E. F. Gillio, and K. R. Bernetich. "One-Step Resin Transfer Molding of Multi-Functional Composites Consisting of Multiple Resins." Patent application filed with the U.S. Patent Office, 22 October 1997.
3. Gillio, E. F. "Co-Injection Resin Transfer Molding of Hybrid Composites." MS Thesis, University of Delaware, 1998.
4. Gillio, E. F., J. W. Gillespie, Jr., R. F. Eduljee, S. G. Advani, K. R. Bernetich, and B. K. Fink. "Manufacturing of Composites With the Co-injection Process." *Proceedings of the Thirty-Eighth AIAA Structures, Structural Dynamics and Materials Conference*, Kissimmee, FL, 7-10 April 1997.
5. Darcy, H. *Les Fontaines Publiques de la Ville de Dijon*. Dalmont, Paris, 1856.
6. Brusckke, M. V. "A Predictive Model for Permeability and Non-Isothermal Flow of Viscous and Shear-Thinning Fluids in Anisotropic Fibrous Media." Ph.D. Thesis, University of Delaware, 1992.
7. Brusckke, M. V., and S. G. Advani. "A Finite Element/Control Volume Approach to Mold Filling in Anisotropic Porous Media." *Polymer Composites*, vol. 11, no. 6, pp. 398-405, 1990.
8. Liu, B., and S. G. Advani. "Operator Splitting Scheme for 3-D Temperature Solution Based on 2-D Flow Approximation." *Computational Mechanics*, vol. 38, pp. 74-82, 1995.
9. Liu, B., S. Bickerton, and S. G. Advani. "Modeling and Simulation of RTM: Gate Control, Venting and Dry Spot Prediction." *Composites Manufacturing*, vol. 27, no. 2, pp. 135-141, 1995.
10. Maier, R. S., T. F. Rohaly, S. G. Advani, and K. D. Fickie. "A Fast Numerical Method for Isothermal Resin Transfer Mold Filling." *International Journal of Numerical Methods in Engineering*, vol. 39, pp. 1405-1422, 1996.
11. Brusckke, M. V., and S. G. Advani. "A Numerical Approach to Model Non-Isothermal, Viscous Flow With Free Surfaces Through Fibrous Media." *International Journal of Numerical Methods in Fluids*, vol. 19, pp. 575-603, 1994.

12. Brusckke, M. V., and S. G. Advani. "RTM: Filling Simulation of Complex Three-Dimensional Shell-Like Structures." *SAMPE Quarterly*, vol. 23, no. 1, pp. 2-11, 1991.

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	DEFENSE TECHNICAL INFORMATION CENTER DTIC DDA 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218
1	HQDA DAMO FDQ D SCHMIDT 400 ARMY PENTAGON WASHINGTON DC 20310-0460
1	OSD OUSD(A&T)/ODDDR&E(R) R J TREW THE PENTAGON WASHINGTON DC 20301-7100
1	DPTY CG FOR RDA US ARMY MATERIEL CMD AMCRDA 5001 EISENHOWER AVE ALEXANDRIA VA 22333-0001
1	INST FOR ADVNCD TCHNLGY THE UNIV OF TEXAS AT AUSTIN PO BOX 202797 AUSTIN TX 78720-2797
1	DARPA B KASPAR 3701 N FAIRFAX DR ARLINGTON VA 22203-1714
1	NAVAL SURFACE WARFARE CTR CODE B07 J PENNELLA 17320 DAHLGREN RD BLDG 1470 RM 1101 DAHLGREN VA 22448-5100
1	US MILITARY ACADEMY MATH SCI CTR OF EXCELLENCE DEPT OF MATHEMATICAL SCI MADN MATH THAYER HALL WEST POINT NY 10996-1786

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	DIRECTOR US ARMY RESEARCH LAB AMSRL DD J J ROCCHIO 2800 POWDER MILL RD ADELPHI MD 20783-1197
1	DIRECTOR US ARMY RESEARCH LAB AMSRL CS AS (RECORDS MGMT) 2800 POWDER MILL RD ADELPHI MD 20783-1145
3	DIRECTOR US ARMY RESEARCH LAB AMSRL CI LL 2800 POWDER MILL RD ADELPHI MD 20783-1145
	<u>ABERDEEN PROVING GROUND</u>
4	DIR USARL AMSRL CI LP (BLDG 305)

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO OF. COPIES</u>	<u>ORGANIZATION</u>
1	DIRECTOR USARL AMSRL CP CA D SNIDER 2800 POWDER MILL RD ADELPHI MD 20783	5	COMMANDER USA ARDEC AMSTA AR CCH S MUSALLI R CARR M LUCIANO T LOUCEIRO PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER USA ARDEC AMSTA AR FSE T GORA PICATINNY ARSENAL NJ 07806-5000	4	COMMANDER USA ARDEC AMSTA AR (2CPS) E FENNEL (2 CPS) PICATINNY ARSENAL NJ 07806-5000
3	COMMANDER USA ARDEC AMSTA AR TD PICATINNY ARSENAL NJ 078806-5000	1	COMMANDER USA ARDEC AMSTA AR CCH P J LUTZ PICATINNY ARSENAL NJ 07806-5000
5	COMMANDER USA TACOM AMSTA JSK S GOODMAN J FLORENCE AMSTA TR D B RAJU L HINOJOSA D OSTBERG WARREN MI 48397-5000	1	COMMANDER USA ARDEC AMSTA AR FSF T C LIVECCHIA PICATINNY ARSENAL NJ 07806-5000
5	PM SADARM SFAE GCSS SD COL B ELLIS M DEVINE W DEMASSI J PRITCHARD S HROWNAK PICATINNY ARSENAL NJ 07806-5000	1	COMMANDER USA ARDEC AMSTA AR QAC T/C C PATEL PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER USA ARDEC F MCLAUGHLIN PICATINNY ARSENAL NJ 07806-5000	2	COMMANDER USA ARDEC AMSTA AR M D DEMELLA F DIORIO PICATINNY ARSENAL NJ 07806-5000

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO OF. COPIES</u>	<u>ORGANIZATION</u>
3	COMMANDER USA ARDEC AMSTA AR FSA A WARNASH B MACHAK M CHIEFA PICATINNY ARSENAL NJ 07806-5000	1	COMMANDER USA BELVOIR RD&E CTR STRBE JBC FT BELVOIR VA 22060-5606
1	COMMANDER SMCWV QAE Q B VANINA BLDG 44 WATERVLIET ARSENAL WATERVLIET NY 12189-4050	2	COMMANDER USA ARDEC AMSTA AR FSB G M SCHIKSNIS D CARLUCCI PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER SMCWV SPM T MCCLOSKEY BLDG 253 WATERVLIET ARSENAL WATERVLIET NY 12189-4050	1	US ARMY COLD REGIONS RESEARCH & ENGINEERING CTR P DUTTA 72 LYME RD HANVOVER NH 03755
8	DIRECTORECTOR BENET LABORATORIES AMSTA AR CCB J KEANE J BATTAGLIA J VASILAKIS G FFIAR V MONTVORI G DANDREA R HASENBEIN AMSTA AR CCB R S SOPOK WATERVLIET NY 12189-4050	1	DIRECTOR USARL AMSRL WT L D WOODBURY 2800 POWDER MILL RD ADELPHI MD 20783-1145
1	COMMANDER SMCWV QA QS K INSCO WATERVLIET NY 12189-4050	1	COMMANDER USA MICOM AMSMI RD W MCCORKLE REDSTONE ARSENAL AL 35898-5247
1	COMMANDER PRODUCTION BASE MODERN ACTY USA ARDEC AMSMC PBM K PICATINNY ARSENAL NJ 07806-5000	1	COMMANDER USA MICOM AMSMI RD ST P DOYLE REDSTONE ARSENAL AL 35898-5247
		3	US ARMY RESEARCH OFFICE A CROWSON K LOGAN J CHANDRA PO BOX 12211 RESEARCH TRIANGLE PARK NC 27709-2211

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO OF. COPIES</u>	<u>ORGANIZATION</u>
3	US ARMY RESEARCH OFFICE ENGINEERING SCIENCES DIV R SINGLETON G ANDERSON K IYER PO BOX 12211 RESEARCH TRIANGLE PARK NC 27709-2211	2	COMMANDER DARPA S WAX 2701 N FAIRFAX DR ARLINGTON VA 22203-1714
5	PM TMAS SFAE GSSC TMA COL PAWLICKI K KIMKER E KOPACZ R ROESER B DORCY PICATINNY ARSENAL NJ 07806-5000	6	COMMANDER WRIGHT PATTERSON AFB WL FIV A MAYER WL MLBM S DONALDSON T BENSON-TOLLE C BROWNING J MCCOY F ABRAMS 2941 P ST STE 1 DAYTON OH 45433
1	PM TMAS SFAE GSSC TMA SMD R KOWALSKI PICATINNY ARSENAL NJ 07806-5000	2	NAVAL SURFACE WARFARE CTR DAHLGREN DIV CODE G06 R HUBBARD CODE G 33 C DAHLGREN VA 22448
3	PEO FIELD ARTILLERY SYSTEMS SFAE FAS PM H GOLDMAN T MCWILLIAMS T LINDSAY PICATINNY ARSENAL NJ 07806-5000	1	NAVAL RESEARCH LAB I WOLOCK CODE 6383 WASHINGTON DC 20375-5000
2	PM CRUSADER G DELCOCO J SHIELDS PICATINNY ARSENAL NJ 07806-5000	1	OFFICE OF NAVAL RESEARCH MECH DIV Y RAJAPAKSE CODE 1132SM ARLINGTON VA 22271
3	NASA LANGLEY RESEARCH CTR MS 266 AMSRL VS W ELBER F BARTLETT JR C DAVILA HAMPTON VA 23681-0001	1	NAVAL SURFACE WARFARE CTR CRANE DIV M JOHNSON CODE 20H4 LOUISVILLE KY 40214-5245
		1	DAVID TAYLOR RESEARCH CTR SHIP STRUCTURES & PROTECTION DEPT J CORRADO CODE 1702 BETHESDA MD 20084
		2	DAVID TAYLOR RESEARCH CTR R ROCKWELL W PHYLLAIER BETHESDA MD 20054-5000

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO OF. COPIES</u>	<u>ORGANIZATION</u>
1	DEFENSE NUCLEAR AGENCY INNOVATIVE CONCEPTS DIV R ROHR 6801 TELEGRAPH RD ALEXANDRIA VA 22310-3398	2	DIRECTOR LLNL F ADDESSIO MS B216 J REPPA MS F668 PO BOX 1633 LOS ALAMOS NM 87545
1	EXPEDITIONARY WARFARE DIV N85 F SHOUP 2000 NAVY PENTAGON WASHINGTON DC 20350-2000	3	UNITED DEFENSE LP 4800 EAST RIVER DR P JANKE MS170 T GIOVANETTI MS236 B VAN WYK MS 389 MINNEAPOLIS MN 55421-1498
1	OFFICE OF NAVAL RESEARCH D SIEGEL 351 800 N QUINCY ST ARLINGTON VA 22217-5660	4	DIRECTOR SANDIA NATIONAL LAB APPLIED MECHANICS DEPT DIV 8241 W KAWAHARA K PERANO D DAWSON P NIELAN PO BOX 969 LIVERMORE CA 94550-0096
7	NAVAL SURFACE WARFARE CTR J H FRANCIS CODE G30 D WILSON CODE G32 R D COOPER CODE G32 E ROWE CODE G33 T DURAN CODE G33 L DE SIMONE CODE G33 DAHLGREN VA 22448	1	BATTALLE C R HARGREAVES 505 KNIG AVE COLUMBUS OH 43201-2681
1	COMMANDER NAVAL SEA SYSTEM CMD P LIESE 2351 JEFFERSON DAVIS HIGHWAY ARLINGTON VA 22242-5160	1	PACIFIC NORTHWEST LAB M SMITH PO BOX 999 RICHLAND WA 99352
1	NAVAL SURFACE WARFARE CTR M E LACY CODE B02 17320 DAHLGREN RD DAHLGREN VA 22448	1	LLNL M MURPHY PO BOX 808 L 282 LIVERMORE CA 94550
1	NAVAL WARFARE SURFACE CTR TECH LIBRARY CODE 323 17320 DAHLGREN RD DAHLGREN VA 22448	10	UNIV OF DELAWARE CTR FOR OCMPOSITE MATERIALS J GILLESPIE 201 SPENCER LAB NEWARK DE 19716
4	DIR LLNL R CHRISTENSEN S DETERESA F MAGMESS M FINGER PO BOX 808 LIVERMORE CA 94550		

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO OF. COPIES</u>	<u>ORGANIZATION</u>
2	THE U OF TEXAS AT AUSTIN CTR ELECTROMECHANICS A WALLIS J KITZMILLER 10100 BURNET RD AUSTIN TX 78758-4497	1	NOESIS INC 1110 N GLEBE RD STE 250 ARLINGTON VA 22201-4795
1	AAI CORPORATION T G STASTNY PO BOX 126 HUNT VALLEY MD 21030-0126	1	ARROW TECH ASSO 1233 SHELBURNE RD STE D 8 SOUTH BURLINGTON VT 05403-7700
1	SAIC D DAKIN 2200 POWELL ST STE 1090 EMERYVILLE CA 94608	5	GEN CORP AEROJET D PILLASCH T COULTER C FLYNN D RUBAREZUL M GREINER 1100 WEST HOLLYVALE ST AZUSA CA 91702-0296
1	SAIC M PALMER 2109 AIR PARK RD S E ALBUQUERQUE NM 87106	1	NIST STRUCTURE & MECHANICS GRP POLYMER DIV POLYMERS RM A209 G MCKENNA GAITHERSBURG MD 20899
1	SAIC R ACEBAL 1225 JOHNSON FERRY RD STE 100 MARIETTA GA 30068	1	GENERAL DYNAMICS LAND SYSTEM DIVISION D BARTLE PO BOX 1901 WARREN MI 48090
1	SAIC G CHRYSSOMALLIS 3800 W 80TH ST STE 1090 BLOOMINGTON MN 55431	4	INSTITUTE FOR ADVANCED TECHNOLOGY H FAIR P SULLIVAN W REINECKE I MCNAB 4030 2 W BRAKER LN AUSTIN TX 78759
6	ALLIANT TECHSYSTEMS INC C CANDLAND R BECKER L LEE R LONG D KAMDAR G KASSUELKE 600 2ND ST NE HOPKINS MN 55343-8367	1	PM ADVANCED CONCEPTS LORAL VOUGHT SYSTEMS J TAYLOR MS WT 21 PO BOX 650003 DALLAS TX 76265-0003
1	CUSTOM ANALYTICAL ENGR SYS INC A ALEXANDER 13000 TENSOR LANE NE FLINTSTONE MD 21530		

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO OF. COPIES</u>	<u>ORGANIZATION</u>
2	UNITED DEFENSE LP P PARA G THOMASA 1107 COLEMAN AVE BOX 367 SAN JOSE CA 95103	4	NIST POLYMERS DIVISION R PARNAS J DUNKERS M VANLANDINGHAM D HUNSTON GAITHERSBURG MD 20899
1	MARINE CORPS SYSTEMS CMD PM GROUND WPNS COL R OWEN 2083 BARNETT AVE STE 315 QUANTICO VA 22134-5000	1	OAK RIDGE NATIONAL LAB A WERESZCZAK BLDG 4515 MS 6069 PO BOX 2008 OAKRIDGE TN 37831-6064
1	OFFICE OF NAVAL RES J KELLY 800 NORTH QUINCEY ST ARLINGTON VA 22217-5000	1	COMMANDER USA ARDEC INDUSTRIAL ECOLOGY CTR T SACHAR BLDG 172 PICATINNY ARSENAL NJ 07806-5000
1	NAVSEE OJRI G CAMPONESCHI 2351 JEFFERSON DAVIS HWY ARLINGTON VA 22242-5160	1	COMMANDER USA ATCOM AVIATION APPLIED TECH DIR J SCHUCK FT EUSTIS VA 23604
1	USAF WL MLS O L A HAKIM 5525 BAILEY LOOP 243E MCCLELLAN AFB CA 55552	1	COMMANDER USA ARDEC AMSTA AR SRE D YEE PICATINNY ARSENAL NJ 07806-5000
1	NASA LANGLEY J MASTERS MS 389 HAMPTON VA 23662-5225	1	COMMANDER USA ARDEC AMSTA AR QAC T D RIGOGLIOSO BLDG 354 M829E3 IPT PICATINNY ARSENAL NJ 07806-5000
2	FAA TECH CTR D OPLINGER AAR 431 P SHYPRYKEVICH AAR 431 ATLANTIC CITY NJ 08405		
1	NASA LANGLEY RC CC POE MS 188E NEWPORT NEWS VA 23608		
1	USAF WL MLBC E SHINN 2941 PST STE 1 WRIGHT PATTERSON AFB OH 45433-7750		

NO. OF  
COPIES      ORGANIZATION

7      COMMANDER  
USA ARDEC  
AMSTA AR CCH B  
B KONRAD  
E RIVERA  
G EUSTICE  
S PATEL  
G WAGNECZ  
R SAYER  
F CHANG  
BLDG 65  
PICATINNY ARSENAL NJ  
07806-5000

6      DIRECTOR  
US ARMY RESEARCH LAB  
AMSRL WM MB  
A ABRAHAMIAN  
M BERMAN  
A FRYDMAN  
T LI  
W MCINTOSH  
E SZYMANSKI  
2800 POWDER MILL RD  
ADELPHI MD 20783-1197

ABERDEEN PROVING GROUND

67      DIR USARL  
AMSRL CI  
AMSRL CI C  
W STUREK  
AMSRL CI CB  
R KASTE  
AMSRL CI S  
A MARK  
AMSRL SL B  
AMSRL SL BA  
AMSRL SL BE  
D BELY  
AMSRL WM B  
A HORST  
E SCHMIDT  
AMSRL WM BE  
G WREN  
C LEVERITT  
D KOOKER

NO OF.  
COPIES      ORGANIZATION

AMSRL WM BC  
P PLOSTINS  
D LYON  
J NEWILL  
AMSRL WM BD  
S WILKERSON  
R FIFER  
B FORCH  
R PESCE RODRIGUEZ  
B RICE  
AMSRL WM  
D VIECHNICKI  
G HAGNAUER  
J MCCAULEY  
AMSRL WM MA  
R SHUFORD  
S MCKNIGHT  
L GHORSE  
AMSRL WM MB  
V HARIK  
J SANDS  
W DRYSDALE  
J BENDER  
T BLANAS  
T BOGETTI  
R BOSSOLI  
L BURTON  
S CORNELISON  
P DEHMER  
R DOOLEY  
B FINK  
G GAZONAS  
S GHORSE  
D GRANVILLE  
D HOPKINS  
C HOPPEL  
D HENRY  
R KASTE  
M LEADORE  
R LIEB  
E RIGAS  
D SPAGNUOLO  
W SPURGEON  
J TZENG  
AMSRL WM MC  
J BEATTY  
AMSRL WM MD  
W ROY  
AMSRL WM T  
B BURNS

NO. OF  
COPIES      ORGANIZATION

ABERDEEN PROVING GROUND (CONT)

AMSRL WM TA  
    W GILLICH  
    E RAPACKI  
    T HAVEL  
AMSRL WM TC  
    R COATES  
    W DE ROSSET  
AMSRL WM TD  
    W BRUCHEY  
    A D GUPTA  
AMSRL WM BB  
    H ROGERS  
AMSRL WM BA  
    F BRANDON  
    W D AMICO  
AMSRL WM BR  
    J BORNSTEIN  
AMSRL WM TE  
    A NILER  
AMSRL WM BF  
    J LACETERA

INTENTIONALLY LEFT BLANK.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE December 1999	3. REPORT TYPE AND DATES COVERED Final, January 1997 - January 1998		
4. TITLE AND SUBTITLE The Role of Transverse Flow in Co-Injection Resin Transfer Molding			5. FUNDING NUMBERS AH42	
6. AUTHOR(S) Bruce K. Fink, Emanuele F. Gillio,* Suresh G. Advani,* and John W. Gillespie Jr.*				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRL-WM-MB Aberdeen Proving Ground, MD 21005-5069			8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TR-2135	
9. SPONSORING/MONITORING AGENCY NAMES(S) AND ADDRESS(ES)			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES *University of Delaware, Newark, DE 19716				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) A co-injection resin transfer molding (CIRTM) process has been developed at the U.S. Army Research Laboratory (ARL) in collaboration with the University of Delaware. It enables two or more resins to be simultaneously injected into a mold filled with a stationary fiber preform. This process allows for the manufacturing of cocured multilayer multiresin structures in a single processing step. A separation layer is used to provide resin compatibility during cure and to control resin mixing. In this study, scaling issues relating the role of transverse permeability in resin mixing are investigated. This report presents two different approaches taken to understand the causes of transverse flow and to quantify the amount of transverse flow. The first approach is a one-dimensional (1-D) model, which explains the important parameters that govern the flow in CIRTM. The second approach is based on an existing finite element code, which is modified to allow for the injection of multiple resins. The total amount of transverse flow was quantified using the finite element code. This research shows that the CIRTM process requires a totally impermeable separation layer if CIRTM is used to manufacture large parts and/or if the resins injected have significantly different viscosities.				
14. SUBJECT TERMS co-injection resin transfer molding, vinyl ester, phenolic, flammability, composite materials			15. NUMBER OF PAGES 31	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT SAR	

INTENTIONALLY LEFT BLANK.

## USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number/Author ARL-TR-2135 (Fink) Date of Report December 1999
2. Date Report Received \_\_\_\_\_
3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_
4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_
5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_
6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

CURRENT  
ADDRESS

\_\_\_\_\_  
Organization

\_\_\_\_\_  
Name

\_\_\_\_\_  
E-mail Name

\_\_\_\_\_  
Street or P.O. Box No.

\_\_\_\_\_  
City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD  
ADDRESS

\_\_\_\_\_  
Organization

\_\_\_\_\_  
Name

\_\_\_\_\_  
Street or P.O. Box No.

\_\_\_\_\_  
City, State, Zip Code

(Remove this sheet, fold as indicated, tape closed, and mail.)  
**(DO NOT STAPLE)**