

Army Research Laboratory

Aberdeen Proving Ground, MD 21005-5066

ARL-MR-492

September 2000

Deviation Effect of an In-Bore Centerline on a 5-Inch Naval Gun

Thomas F. Erline

Weapons and Materials Research Directorate, ARL

Approved for public release; distribution is unlimited.

Abstract

A naval cannon was analyzed with the Little RASCAL gun dynamics program to predict shot exit conditions. There appeared to be a sharp manufacturing bend in the barrel's vertical plane. The Little RASCAL program makes modeling many hypothetical cases easy. This report compares the projectile and barrel interacting forces with and without the effects of the sharp bend. More importantly, a small sinusoidal variation in the deviation of the barrel centerline preceding the sharp bend presents itself as a detrimental factor by amplifying the lateral forces.

Acknowledgments

The author appreciates the efforts of R. Bowen and R. D. Cooper of Naval Surface Warfare Center Dahlgren Division (NSWCDD) for contacting the U.S. Army Research Laboratory (ARL) to conduct this work. Also, many thanks are extended to T. Marrs and D. Swan of the U.S. Army Aberdeen Test Center (ATC) for performing the centerline measurements at Dahlgren, VA. Last, but not least, Leo L. Fischer of the United Defense Limited Partnership (UDLP) helped this author many times by sharing his expertise of naval weapons.

INTENTIONALLY LEFT BLANK.

Table of Contents

	<u>Page</u>
Acknowledgments	iii
List of Figures	vii
1. Introduction	1
2. Background	1
3. Approach	2
4. Modeling	3
4.1 Gun Model	5
4.2 Projectile Model	5
5. Hypothetical Cases, Discussions, and Results	6
6. Conclusions	11
7. References	13
Distribution List	15
Report Documentation Page	23

INTENTIONALLY LEFT BLANK.

List of Figures

<u>Figure</u>		<u>Page</u>
1.	The EX45 Mod4 Gun Mount	2
2.	The Prototype 5-Inch 62-cal. Barrel S/N 17448 Vertical Centerline	4
3.	Mk64 5-inch Projectile.....	6
4.	Gravity-Free Comparison of Original CL and Modified Low-Slope CL.....	7
5.	Interaction Forces for Original, Droop Only, and the Low-Slope CLs	8
6.	A Small Sinusoidal Shape Evident in the CL Between the Supports	8
7.	A Modified CL Isolates the Bend and Removes the Small Sinusoidal Shape	9
8.	Comparison of the Isolated Bend Forces to the Original Forces and Droop Only....	10
9.	Gravity-Free Comparison of Forces: Isolated Bend CL, Original CL, and Low-Slope CL	10

INTENTIONALLY LEFT BLANK.

1. Introduction

This report considers a number of hypothetical cases where the centerline of a gun barrel changes from a bent state to an unbent state. All other parameters remain the same. In the process of analyzing these hypothetical cases, a concern came up as to why the maximum value of the lateral forces was not significantly changed. It was found that a small sinusoidal variation in the deviation of the centerline of the barrel initiates a projectile rocking frequency that produces higher oscillatory lateral forces. This study can be considered a simple functional analysis. All variables are held constant except for the centerline (the domain). The Little RASCAL gun dynamics code [1] is used as the operator to give the resultant barrel-projectile interaction forces (the range). It is interesting to note that a small sinusoidal wave in a centerline drives lateral forces more than a single bend in a centerline. This finding is subject to the limitations of the assumptions within the Little RASCAL code.

The basis of the analysis starts with the simulated firing of the Mk64 projectile from the U.S. Navy's new 5-inch 62-cal. gun mount, the EX45 Mod4 [2]. A prototype 62-cal. barrel (serial number 17448) was mated to the EX45 Mod4 gun mount and was recently range tested. The U.S. Army Research Laboratory (ARL) Little RASCAL gun and projectile dynamics simulation program was used to model this gun system's lateral dynamics and provide the shot exit conditions when fired at service charge. This work was sponsored by the Naval Surface Warfare Center Dahlgren Division (NSWCDD) [3] as part of the Naval Surface Fire Support (NSFS) program.

2. Background

The objectives of the NSFS program require that 5-inch naval guns provide fire support from greater off-shore distances and hit targets with increased lethality. The key elements satisfying these objectives are an upgrade to the existing 5-inch 54-cal. Mk45 Mod2 gun mount and the development of the rocket-assisted projectiles (RAP).

NSFS modifications to the Mk45 gun system include structural enhancements to increase the allowable chamber pressure and ballistic impulse, replacement of the 54-cal. barrel with a 62-cal. barrel, and development of an adaptive digital control system that supports a new Gun Computing System (GCS) and RAP interface requirements. These modifications, plus development of certain RAPs, will allow the gun system to support engagement ranges of up to 63 nautical miles for certain RAP rounds and up to 21 nautical miles with future ballistic projectiles. Figure 1 illustrates the components of the EX45 Mod4 gun mount.




Figure 1. The EX45 Mod4 Gun Mount.

The 5-inch 62-cal. EX45 Mod4 gun mount is being developed for the U.S. Navy by the Armament Systems Division of United Defense Limited Partnership (UDLP). The original work supports a recent firing test at NSWCDD, Dahlgren, VA.

3. Approach

The Little RASCAL gun and projectile dynamics program was chosen for this effort because it can produce projectile exit conditions in a timely manner. Gun dynamics predictions of barrel

motion made by Little RASCAL agree quite well with experimental results over a wide range of gun system sizes and types [4].

In addition, the 5-inch 54-cal. Mk45 Mod2 had been previously modeled [5] using the Little RASCAL code, and only minor changes to the gun mount and gun barrel data were required to accurately model the Mod4 gun mount. The gun system information input required includes the geometry and mass description of the gun barrel and breech along with breech center-of-gravity (CG) offsets, trunnion and elevation support locations, and their equivalent spring constants. Information concerning the dimensional mass properties of the 5-inch 62-cal. gun barrel, along with the information necessary to describe the Mod4 gun mount configuration, was supplied by UDLP [2].

The final gun system data requirement is a description of the variations in the gun barrel centerline. (The standard centerline definition is the deviation of bore center off of a straight line, starting at the center of the forcing cone and directed to the center of the muzzle. Recently, Army ballisticians have been reorienting the centerline axis, such that the support positions used at measurement time define the straight line axis. This configuration shows the wanderings of the centerline after the support up to the muzzle.) The centerline of the prototype 62-cal. barrel, S/N17448, displayed in Figure 2, was supported at 4,800 mm and 7,000 mm from the muzzle and was measured by the U.S. Army Aberdeen Test Center (ATC) personnel at Dahlgren, VA [5]. Only the vertical component of the centerline is displayed because this is the plane where the perceived hard-pressed bend is evident. In Figure 2, the solid line indicates the vertical centerline (CL) without gravity droop, the dashed line shows the CL with droop, and the line with "x" symbols shows the simple droop from the indicated supports.

4. Modeling

The Little RASCAL gun and projectile dynamics program is a dynamic displacement code employing a direct structural dynamics analysis approach to the simulation of firing a




Figure 2. The Prototype 5-Inch 62-cal. Barrel S/N 17448 Vertical Centerline.

projectile from a gun. The program is capable of simulating the inertial loading conditions brought about by the projectile interacting with the barrel in a plane as it accelerates the length of the gun tube. The tracking of the inertial loading in-bore allows the program to predict initial launch conditions of the projectile at shot exit. In addition, projectile and gun flexural response can be observed.

Both the gun system and the projectile are modeled using a series of equally spaced cylindrical elements. The element nodes are centered and assigned equivalent mass and stiffness values that are based on standard engineering formulas. Inertial forces and flexural forces are calculated for this simplified description. Flexure at each node is approximated using a second-order finite difference method that also computes the bending forces. Transverse nodal accelerations caused by these forces are integrated once with respect to time to obtain transverse nodal velocities and again to obtain lateral node displacements. Loads induced by pressure effects, mounting conditions, breech CG offset, and the projectile's interaction with the barrel forces are taken into account. This algorithm does not emulate true balloting as the projectile is modeled in the bore without gaps and is forced to follow the dynamically changing centerline. Finally, the barrel is considered smoothbore.

The gun system (which includes the breech, barrel, and two gun supports) and the projectile system are two separate models. They are accounted for individually as finite structural systems, except for a variational algorithm that handles their interaction. The interaction of the projectile with the barrel occurs through contact points. The two contact points defined on the projectile are usually positioned where they occur geometrically. The two projectile contact point positions on the barrel are dynamic and change as the projectile traverses the bore. The gun system model and the projectile model are two separate, flexible entities, with each projectile contact point requiring a user-supplied spring constant. The spring constants serve to define the interface loads between the projectile model and the gun model. There is an algorithm within the program that adjusts the time step to ensure the last projectile spring contact interacts with the node that represents the muzzle of the gun.

4.1 Gun Model. Gun system information input includes the geometry and mass description of the gun barrel and breech, along with breech CG offsets, trunnion and elevation support locations, and their equivalent spring constants. The breech assembly of the EX45 Mod4 weighs 1,598 kg (3,521 lb). The axial location of the breech CG is 436.9 mm (17.2 in) from the rear face of the breech (RFB), and the breech CG with the breech block in the firing position is offset 5.49 mm (0.216 in) vertically and -2.72 mm (-0.107 in) horizontally. The trunnion supports are located 577.8 mm (22.75 in) forward of the rear face of the breech assembly and were assigned a spring constant of 5.6^8 N/m (3,200,000 lb/in). The effective elevation support of the gun assembly is located 1406.3 mm (55.68 in) forward of the rear breech face and was assigned a spring constant of 23.8^6 N/m (135,800 lb/in). The values for the spring constants of the trunnions and elevation support were supplied by UDLP and were derived from a finite element model used to analyze the gun structure under shipboard shock and vibrations.

4.2 Projectile Model. The projectile used in the firing tests is the standard Mk64 high-explosive round. This short wheelbase, stiff projectile body, shown in Figure 3, was modeled previously [5]. The physical properties of the Mk64 are length - 662.5 mm (26.082 in), weight - 31.61 kg (68.70 lb), and center of gravity - 420.6 mm (16.560 in) from the nose. The




Figure 3. Mk64 5-inch Projectile.

required spring parameters are forward contact - 342.0 mm (13.46 in) from nose, forward spring - 2.08^8 N/m (1.185⁶ lb/in), aft contact - 571.0 mm (22.480 in) from nose, and the aft spring - 1.97^8 N/m (1.125⁶ lb/in).

5. Hypothetical Cases, Discussions, and Results

Major cannon-producing plants, such as the one in Louisville, KY, for the U.S. Navy, routinely practice pressing or bending cannon barrels in the manufacturing process. After the last major pressing operation, the barrel is rotated about the axis to find the muzzle high point, and then the barrel is indexed up. The evidence of what appears to be a hard bend just before the support point of 4,800 mm from the muzzle can be noted in Figure 2, but is best observed in Figure 4 where the vertical CL is displayed without gravity.

The first set of hypothetical cases starts with the original vertical CL with gravity, noted in Figure 2, and a modified CL called "low-slope," where the hard bend is removed. By constructing a straight line from the support to the muzzle and storing the differences, the remainder of the centerline can be reconstructed anywhere. In this case, as shown in Figure 4,




Figure 4. Gravity-Free Comparison of Original CL and Modified Low-Slope CL.

the low-slope line positions the muzzle at zero displacement. The last CL considered for this first set is the simple droop case, plotted in Figure 2.

For simplicity, only the projectile front contact forces will be presented in this report. The forces are shown in the time domain. (Note that the projectile front contact reaches the bend 7.4 ms after shot start.) The projectile front contact forces in Figure 5 show that there is a reduction in magnitude for the two CLs other than the original v-17448 CL. However, the force response for the low-slope case is not significantly different from the original case. There was an expectation of a reduced magnitude in the lateral force for the low-slope case. The forces for the droop-only CL case produce the lowest lateral loads and probably represent a best-case scenario because this CL is a low frequency smooth curve.

The CLs of Figure 2 are displayed again in Figure 6 with scales changed to show a closeup of the first 2.5 m of projectile travel. In Figure 6, the CL has a peak-to-peak sinusoidal wave in this region of only 0.1 mm. This small sinusoidal wave causes the first 7.4 ms of lateral disturbances.

To determine the magnitude of the disturbance force due to the bend, a hypothetical case is made up in which the first 2.2 m of the CL without gravity is not allowed to deviate from the




Figure 5. Interaction Forces for Original, Droop Only, and the Low-Slope CLs.




Figure 6. A Small Sinusoidal Shape Evident in the CL Between the Supports.

axis.* Next, with gravity applied to this straightened hypothetical CL, the first 2.2 m of the projectile travel follows the droop curve before the projectile front contact meets the bend point. These hypothetical centerline cases are illustrated in Figure 7.




Figure 7. A Modified CL Isolates the Bend and Removes the Small Sinusoidal Shape.

In Figure 8, the barrel-projectile interaction forces are shown in the vertical plane for three CL cases. Two of the cases are from the hypothetical cases shown in Figure 7, the simple droop CL and the isolated bend CL, and the third is the original CL. In this example, the projectile interaction forces of the isolated bend case follow the droop case until the bend is encountered, then the peak of the isolated bend case falls significantly in comparison. However, the peak of the original CL case is significantly greater than both of the other cases. Since the forces noted for the original CL are about two times higher than the isolated bend case, the small sinusoidal shape preceding the bend is amplifying the force response. The small sinusoidal wave in the original CL initiates an earlier force response which exacerbates the force magnitudes throughout the entire in-bore loading cycle.

* This removes the sinusoidal wave during the initial travel and isolates the bend.




Figure 8. Comparison of the Isolated Bend Forces to the Original Forces and Droop Only.

After eliminating the force response due to gravity droop, the following hypothetical cases are compared in a gravity-free field: the isolated bend CL (noted in Figure 7), the original CL (Figure 4), and the low-slope CL (Figure 4). The forces for these cases, shown in Figure 9, are most interesting because the two curves that contain the small sinusoidal shape (the original CL and the low-slope CL) have their forces almost entirely overlapping each other. The simple isolated bend case forces start later in the in-bore cycle and present lower magnitudes than the other two cases.




Figure 9. Gravity-Free Comparison of Forces: Isolated Bend CL, Original CL, and Low-Slope CL.

6. Conclusions

The prototype 62-cal. naval cannon (S/N 17448) was analyzed with the Little RASCAL gun dynamics program. To examine the barrel-projectile interacting forces, hypothetical cases were used for removing the bend and what was originally believed to be an insignificant, small sinusoidal variation in the centerline preceding the bend. This analysis suggests that

- a single, isolated bend in a gun barrel centerline may not be conducive to generating large lateral loads, but
- a small sine wave in a gun barrel centerline can significantly amplify lateral loads.

The Little RASCAL program is an ideal vehicle for running many hypothetical cases. Even though the Little RASCAL is a first-order analysis code, it is likely that higher-order numerical solutions would yield similar trends.

INTENTIONALLY LEFT BLANK.

7. References

1. Erline, T. F., M. D. Kregel, and M. Pantano. "Gun and Projectile Flexural Dynamics Modeled by the Little RASCAL - A User's Manual." BRL-TR-3122, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, July 1990.
2. Fischer, L. Personal communication. United Defense, LP, Minneapolis, MN, April 1998.
3. Bowen, R., and R. D. Cooper. Personal communication. U.S. Naval Surface Warfare Center - Dahlgren Division, Dahlgren, VA, April 1998.
4. Erline, T. F., and M. D. Kregel. "Modeling Gun Dynamics With Dominant Loads." BRL-MR-3683, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, July 1988.
5. Erline, T. F., and L. L. Fischer. "First Order Dynamic Tools for Rapid Assessment of Small Changes to Major Gun and Projectile Dynamic Parameters." *Proceedings of the Eighth U.S. Army Symposium On Gun Dynamics*, ARCCB-SP-96032, May 1996.

INTENTIONALLY LEFT BLANK.

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	DEFENSE TECHNICAL INFORMATION CENTER DTIC DDA 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218	1	DIRECTOR US ARMY RESEARCH LAB AMSRL D D R SMITH 2800 POWDER MILL RD ADELPHI MD 20783-1197
1	HQDA DAMO FDT 400 ARMY PENTAGON WASHINGTON DC 20310-0460	1	DIRECTOR US ARMY RESEARCH LAB AMSRL DD 2800 POWDER MILL RD ADELPHI MD 20783-1197
1	OSD OUSD(A&T)/ODDDR&E(R) R J TREW THE PENTAGON WASHINGTON DC 20301-7100	1	DIRECTOR US ARMY RESEARCH LAB AMSRL CI AI R (RECORDS MGMT) 2800 POWDER MILL RD ADELPHI MD 20783-1145
1	DPTY CG FOR RDA US ARMY MATERIEL CMD AMCRDA 5001 EISENHOWER AVE ALEXANDRIA VA 22333-0001	3	DIRECTOR US ARMY RESEARCH LAB AMSRL CI LL 2800 POWDER MILL RD ADELPHI MD 20783-1145
1	INST FOR ADVNCD TCHNLGY THE UNIV OF TEXAS AT AUSTIN PO BOX 202797 AUSTIN TX 78720-2797	1	DIRECTOR US ARMY RESEARCH LAB AMSRL CI AP 2800 POWDER MILL RD ADELPHI MD 20783-1197
1	DARPA B KASPAR 3701 N FAIRFAX DR ARLINGTON VA 22203-1714		
			<u>ABERDEEN PROVING GROUND</u>
1	NAVAL SURFACE WARFARE CTR CODE B07 J PENNELLA 17320 DAHLGREN RD BLDG 1470 RM 1101 DAHLGREN VA 22448-5100	4	DIR USARL AMSRL CI LP (BLDG 305)
1	US MILITARY ACADEMY MATH SCI CTR OF EXCELLENCE MADN MATH MAJ HUBER THAYER HALL WEST POINT NY 10996-1786		

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
7	COMMANDER US ARMY TACOM ARDEC AMSTA AR CCH B R SAYER B KONRAD E RIVERA G EUSTICE S PATEL G WAGNECZ F CHANG PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER US ARMY TACOM ARDEC AMSTA AR FSF T BLDG 65 C LIVECCHIA PICATINNY ARSENAL NJ 07806-5000
3	COMMANDER US ARMY TACOM ARDEC AMSTA AR CC BLDG 65 E GOON G FLEMING G MOSHIER PICATINNY ARSENAL NJ 07806-5000
9	COMMANDER US ARMY TACOM ARDEC AMSTA AR CCH A MUSA16LLI P CHRISTIAN R CARR M LUCIANO T LOUZEIRO T R CARR J DELORENZO N KRASNOW S MUSALLI PICATINNY ARSENAL NJ 07806-5000

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
1	PROGRAM EXECUTIVE OFC GRND COMBAT & SPRT SYSTEMS SFAE GCSS W BV S DAVIS WARREN MI 48397-5000
3	COMMANDER US ARMY TACOM ARDEC AMSTA AR FSF DV K PFLEGER R TESTA E LA ROSA PICATINNY ARSENAL NJ 07806-5000
14	COMMANDER US ARMY TACOM ARDEC AMSTA AR FSF T BLDG 382 S CHUNG A FARINA J GRAU B WONG W TOLEDO D PEDERSEN A FIORELLINI E VAZQUEZ C NG M AMORUSO W KOENIG S HAN G MALEJKO J THOMASOVICH PICATINNY ARSENAL NJ 07806-5000
11	ALLIANT TECHSYSTEMS INC R SCHWARTZ N VLAHAKIS D FISCHER R BECKER S BURRETTA C AAKHUS C CANDLAND D KAMDAR G KASSUELKE L LEE R LONG 600 2ND ST NE HOPKINS MN 55343

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
4	ARROW TECH ASSOCIATES INC R WHYTE J WHYTE A HATHAWAY W HATHAWAY 1233 SHELBURNE RD SUITE D8 SOUTH BURLINGTON VT 05403
2	DNA INNOVATIVE CONCEPTS DIV J D HEWITT R ROHR 6801 TELEGRAPH RD ALEXANDRIA VA 22310-3398
2	COMMANDER DARPA J KELLY B WILCOX 3701 N FAIRFAX DR ARLINGTON VA 22310-1714
5	HQDA SARD TR R CHAIT K KOMINOS SARD TT J APPEL F MILTON C NASH WASHINGTON DC 20310-0103
1	PEO ARMAMENTS TMAS AMCPM TMA K KIMKER PICATINNY ARSENAL NJ 07806-5000
1	PEO ARMAMENTS TMAS AMCPM TMA MD K KOWALSKI PICATINNY ARSENAL NJ 07806-5000
2	PM SADARM PICATINNY ARSENAL NJ 07806-5000

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
1	COMMANDER TACOM AMSTA JSK S GOODMAN WARREN MI 48397-5000
1	COMMANDER ARDEC F MCLAUGHLIN PICATINNY ARSENAL NJ 07806-5000
2	COMMANDER ARDEC AMSTA AR CC J HEDDERICH COL SINCLAIR PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER ARDEC AMSTA AR CCH P J LUTZ PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER ARDEC AMSTA AR CCH V E FENNELL PICATINNY ARSENAL NJ 07806-5000
2	COMMANDER ARDEC AMSTA AR FSA B MACHAK A WARNASH PICATINNY ARSENAL NJ 07806-5000
2	COMMANDER ARDEC AMSTA AR FSA M D DEMELLA F DIORIO PICATINNY ARSENAL NJ 07806-5000

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	COMMANDER ARDEC AMSTA AR FSE T GORA PICATINNY ARSENAL NJ 07806-5000
3	COMMANDER ARDEC AMSTA AR TD V LINDNER R PRICE C SPINELLI PICATINNY ARSEANL NJ 07806-5000
1	COMMANDER ARDEC AMSMC PMB K PICATINNY ARSENAL NJ 07806-5000
7	DIRECTOR BENNET LABORATORY AMSTA AR CCB G FFIAR J BATTAGLIA R HASENBEIN J KEANE V MONTVORI J VASILAKIS AMSTA AR CCB R S SOPOK WATERVLIET NY 12189-4050
1	COMMANDER WATERVLIET ARSENAL AMSTA WV QAE Q B VANINA BLDG 253 WATERVLIET NY 12189-4050

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
3	COMMANDER MICOM AMSMI RD W MCCORKLE AMSMI RD ST P DOYLE AMSMI RD ST CN T VANDIVER RSA AL 35898-5247
1	DIRECTOR USA CRREL P DUTTA 72 LYME RD HANOVER NH 03755
5	COMMANDER ARO G ANDERSON J CHANDRA A CROWSON K IYER R SINGLETON PO BOX 12211 RESEARCH TRIANGLE PARK NC 27709-2211
1	COMMANDER USA BELVOIR RD&E CTR STRBE JBC FORT BELVOIR VA 22060-5606
1	USN EXPEDITIONARY WF DIV F SHOUP 2000 NAVY PENTAGON WASHINGTON DC 20350-2000
2	OFFICE OF NAVAL RSRCH CODE 351 D SIEGEL CODE 1132SM Y RAJAPAKSE 800 N QUINCY ST ARLINGTON VA 22217-5660
1	COMMANDER NAVAL RSRCH LAB CODE 6383 I WOLOCK WASHINGTON DC 20375-5000

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
1	COMMANDER NAVAL SEA SYS CMD DLIESE 2531 JEFFERSON DAVIS HWY ARLINGTON VA 22242-5160
10	COMMANDER NSWC CODE G06 CODE G30 J H FRANCIS CODE G32 R D COOPER E WILKERSON D WILSON CODE G33 L DE SIMONE T DORAN R HUBBARD J FRAYSSE E ROWE DAHLGREN VA 22448-5000
1	COMMANDER NSWC CRANE DIV CODE 20H4 M JOHNSON LOUISVILLE KY 40214-5245
3	DAVID TAYLOR RSCH CTR W PHYLLAIER R ROCKWELL CODE 1702 J CORRADO BETHESDA MD 20054-5000
2	AFWL FIV A MAYER MLBM S DONALDSON 2941 P STREET STE 1 DAYTON OH 45433
1	COMMANDER USMC SYS CMD PM GROUND WPNS R OWEN 2083 BARNETT AVE STE 315 QUANTICO VA 22134-5000

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
2	NASA LANGLEY RSCH CTR AMSRL VS MS 266 F BARTLETT JR W ELBER HAMPTON VA 23681-0001
3	DIRECTOR LANL F ADDRESSIO MS B216 J REPPA MS F668 D RABERN MEE 13/MS J576 PO BOX 1663 LOS ALAMOS NM 87545
5	DIRECTOR LLNL R CHRISTENSEN S DETERESA M FINGER F MAGNESS M MURPHY PO BOX 808 LIVERMORE CA 94550-0622
1	DIRECTOR ORNL R M DAVIS PO BOX 2008 OAK RIDGE TN 37831-6195
5	DIRECTOR SNL APPL MECH DEPT DIV 8241 D DAWSON W KAWAHARA P NIELAN K PERANO C ROBINSON PO BOX 969 LIVERMORE CA 94550-0096
1	PACIFIC NW LABS P SMITH PO BOX 999 RICHLAND PA 99352

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
4	INST OF ADVANCED TECH UNIV OF TX AT AUSTIN W REINECKE H FAIR T KIEHNE P SULLIVAN 4030 2 W BRAKER LANE AUSTIN TX 78759-5329
1	SOUTHWEST RSCH INST ENGRNG & MATL SCI DIV J P RIEGEL 6220 CULEBRA RD PO DRAWER 28510 SAN ANTONIO TX 78228-0510
1	UCLA MANE DEPT ENGR IV H T HAHN LOS ANGELES CA 90024-1597
1	UNIV OF TX AT AUSTIN CTR FOR ELECTROMECH J PRICE 10100 BURNET RD AUSTIN TX 78758-4497
1	AAI CORP T G STASTNY PO BOX 126 HUNT VALLEY MD 21030-0126
1	BATTELLE C R HARGREAVES 505 KING AVE COLUMBUS OH 43201-2681
1	BRIGS CO J BACKOFEN 2668 PETERBOROUGH ST HERNDON VA 22071-2443
13	UDLP T GIOVANETTI MAIL STOP 4781 P JANKE MAIL STOP 170 B VANWYK MAIL STOP 389 L FISCHER (10 CPS) 4800 EAST RIVER RD MINNEAPOLIS MN 55421-1498

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
1	GENERAL DYNAMICS LAND SYS DIV D BARTLE PO BOX 1901 WARREN MI 48090
1	CUSTOM ANAL ENGRNG SYS INC A ALEXANDER 13000 TENSOR LANE NE FLINTSTONE MD 21530
1	IAP RSCH INC A CHALLITA 2763 CULVER AVE DAYTON OH 45429
1	INTERFEROMETRICS INC R LARRIVA VP 8150 LEESBURG PIKE VIENNA VA 22100
1	LORAL VOUGHT SYS PM ADVANCED CONCEPTS J TAYLOR MS WT 21 PO BOX 650003 DALLAS TX 76265-0003
2	LORAL VOUGHT SYS K COOK G JACKSON 1701 W MARSHALL DR GRAND PRAIRIE TX 75051
2	MARTIN MARIETTA CORP P DEWAR L SPONAR 230 E GODDARD BLVD KING OF PRUSSIA PA 19406
2	OLIN CORP FLINCHBAUGH DIV E STEINER B STEWART PO BOX 127 RED LION PA 17356
1	NOESIS INC A BOUTZ 1110 N GLEBE RD STE 250 ARLINGTON VA 22201-4795

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	OLIN CORP L WHITMORE 10101 9TH ST NO ST PETERSBURG FL 33702
1	PROJECTILE TECH INC 515 GILES ST HAVRE DE GRACE MD 21078
1	SCIENCE APPL INTERNATL CORP R ACEBAL 1225 JOHNSON FERRY RD STE 100 MARIETTA GA 30068
1	SCIENCE APPL INTERNATL CORP G CHRYSSOMALLIS 3800 W 80TH ST STE 1090 BLOOMINGTON MN 55431
1	SCIENCE APPL INTERNATL CORP D DAKIN 2200 POWLL ST STE 1090 EMERYVILLE CA 94608
1	SCIENCE APPL INTERNATL CORP M PALMER 2109 AIR PARK RD SE ALBUQUERQUE NM 87106
1	SPARTA INC J GLATZ 9455 TOWNE CTR DR SAN DIEGO CA 92121-1964
2	UDLP P PARA G THOMAS 1107 COLEMAN AVE BOX 367 SAN JOSE CA 95103
1	ZERNOW TECH SVCS L ZERNOW 425 W BONITA AVE STE 208 SAN DIMAS CA 91773
1	R EICHELBERGER CONSULTANT 409 W CATHERINE ST BEL AIR MD 21014-3613

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	J HEBERT PO BOX 1072 HUNT VALLEY MD 21030-0126
3	PRIMEX TECHNOLOGIES D DEMAIRE M WILSON L WHITMORE 10101 9TH ST NORTH ST PETERSBURG FL 33702
3	PRIMEX TECHNOLOGIES B STEWART J DUCHEK D OSMENT PO BOX 127 RED LION PA 17356
<u>ABERDEEN PROVING GROUND</u>	
1	DIR USATECOM AMSTE TE F L TELETSKI
1	CDR USAATC STEC LI
4	CDR USATACOM ARDEC AMSTA AR FSF T R LIESKE J MATTS F MIRABELLE J WHITESIDE
3	DIR USAMSA AMXSY CA R NORMAN J CORLEY R THOMPSON
23	DIR USARL AMSRL WM MB W DRYSDALE C HOPPEL L BURTON P KASTE AMSRL WM B E SCHMIDT

NO. OF
COPIES ORGANIZATION

ABERDEEN PROVING GROUND
CONT

AMSRL WM BA
W D AMICO
M BRANDON
L BURKE
AMSRL WM BC
B GUIDOS
D LYON
P PLOSTINS
K SOENCKSEN
D WEBB
J NEWILL
S WILKERSON
T ERLINE
J GARNER
A ZIELINSKI
A MIKHAIL
V OSKAY
B PATTON
M BUNDY
K HEAVEY

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)

2. REPORT DATE

September 2000

3. REPORT TYPE AND DATES COVERED

Final, Mar 98 - Mar 99

4. TITLE AND SUBTITLE

Deviation Effect of an In-Bore Centerline on a 5-Inch Naval Gun

5. FUNDING NUMBERS

IL1622618.AH80

6. AUTHOR(S)

Thomas F. Erline

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

U.S. Army Research Laboratory
ATTN: AMSRL-WM-BC
Aberdeen Proving Ground, MD 21005-5066

8. PERFORMING ORGANIZATION
REPORT NUMBER

ARL-MR-492

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)

10. SPONSORING/MONITORING
AGENCY REPORT NUMBER

11. SUPPLEMENTARY NOTES

12a. DISTRIBUTION/AVAILABILITY STATEMENT

Approved for public release; distribution is unlimited.

12b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)

A naval cannon was analyzed with the Little RASCAL gun dynamics program to predict shot exit conditions. There appeared to be a sharp manufacturing bend in the barrel's vertical plane. The Little RASCAL program makes modeling many hypothetical cases easy. This report compares the projectile and barrel interacting forces with and without the effects of the sharp bend. More importantly, a small sinusoidal variation in the deviation of the barrel centerline preceding the sharp bend presents itself as a detrimental factor by amplifying the lateral forces.

14. SUBJECT TERMS

centerlines, gun dynamics, projectile dynamics

15. NUMBER OF PAGES

26

16. PRICE CODE

17. SECURITY CLASSIFICATION
OF REPORT

UNCLASSIFIED

18. SECURITY CLASSIFICATION
OF THIS PAGE

UNCLASSIFIED

19. SECURITY CLASSIFICATION
OF ABSTRACT

UNCLASSIFIED

20. LIMITATION OF ABSTRACT

UL

INTENTIONALLY LEFT BLANK.

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number/Author ARL-MR-492 (Erline) Date of Report September 2000

2. Date Report Received _____

3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT
ADDRESS

Organization

Name E-mail Name

Street or P.O. Box No.

City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD
ADDRESS

Organization

Name

Street or P.O. Box No.

City, State, Zip Code

(Remove this sheet, fold as indicated, tape closed, and mail.)
(DO NOT STAPLE)

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 0001, APG, MD

POSTAGE WILL BE PAID BY ADDRESSEE

DIRECTOR
US ARMY RESEARCH LABORATORY
ATTN AMSRL WM BC
ABERDEEN PROVING GROUND MD 21005-5066



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

