

ARMY RESEARCH LABORATORY



**Vulnerability/Lethality Server High Level Architecture
(HLA) Interface Control Document**

by Geoffrey C. Sauerborn

ARL-MR-0575

February 2004

NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

DESTRUCTION NOTICE—Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Aberdeen Proving Ground, MD 21005-5066

ARL-MR-0575

February 2004

Vulnerability/Lethality Server High Level Architecture (HLA) Interface Control Document

Geoffrey C. Sauerborn
Weapons and Materials Research Directorate, ARL

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188		
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) February 2004		2. REPORT TYPE Final		3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE Vulnerability/Lethality Server High Level Architecture (HLA) Interface Control Document				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Geoffrey C. Sauerborn (ARL)				5d. PROJECT NUMBER 621618H80	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory Weapons & Materials Research Directorate Aberdeen Proving Ground, MD 21005-5066				8. PERFORMING ORGANIZATION REPORT NUMBER ARL-MR-0575	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT The U.S. Army Research Laboratory (ARL) vulnerability/lethality table look-up server has gone through several iterations of development since first introduced in 1997 (then as the distributed interactive simulation [DIS] lethality communications server). These development iterations represented migration from its original transmission control protocol/internet protocol client/server communication form based in DIS, to a combined DIS-high level architecture (HLA) form used during the 2001 Research, Development, and Engineering Center (RDEC) Federation "CalEx" (calibration experiments) and onto this current form that is all HLA and was designed for the RDEC command "1stApp" (First Application) experiment 2003 and presented in this report. This interface control document (ICD) describes the current state of exposed interface control components of the ARL vulnerability/lethality table look-up server (the server). The ICD describes the interface to an existing implementation of the server (with its look-up table capability). The interface described in this report includes an area that provides for further expansion, allowing delivery of damage descriptions from near real-time physics-based vulnerability models (future dynamic calculation capability).					
15. SUBJECT TERMS distributed modeling and simulation; high level architecture; HLA; vulnerability/lethality server					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UL	18. NUMBER OF PAGES 20	19a. NAME OF RESPONSIBLE PERSON Geoffrey C. Sauerborn
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NUMBER (Include area code) 410-278-8657

Contents

List of Figures	iii
List of Tables	iii
1. Introduction	1
2. Scope	1
3. Simulation Object Model (SOM) Intent	1
3.1 SOM Object Classes	2
3.2 SOM Interaction Classes	2
3.3 Assumptions	4
4. References	10
Distribution List	11

List of Figures

Figure 1. Query and response interaction	3
Figure 2. Resulting damage interaction	4

List of Tables

Table 1. Lethality server class structure	2
Table 2. Object classes (server published)	2
Table 3. Ancillary but required object classes (from RPR FOM)	2
Table 4. Lethality server interaction class structure	3
Table 5. Lethality server interaction: “service.broadcastinfo.lethality.tablelookup”	5
Table 6. Lethality server interaction: “service.query.lethality.tablelookup.parameters”	6
Table 7. Lethality server interaction: “service.query.lethality.tablelookup.results”	7
Table 8. RPR FOM interactions	8
Table 9. Enumerations	8
Table 10. Complex data types	8

INTENTIONALLY LEFT BLANK

1. Introduction

The U.S. Army Research Laboratory (ARL) vulnerability/lethality table look-up server has gone through several iterations of development since first introduced in 1997 (then as the distributed interactive simulation [DIS] lethality communications server) (1). These development iterations represented migration from its original transmission control protocol/internet protocol client/server communication form based in DIS, to a combined DIS-high level architecture (HLA) form used during the 2001 Research, Development, and Engineering Center (RDEC) Federation “CalEx” (calibration experiments) (2) and onto this current form that is all HLA and was designed for the RDEC command “1stApp” (First Application) experiment 2003 and presented in this report (3,4,5,6).

This interface control document (ICD) describes the current state of exposed HLA interface control components of the ARL vulnerability/lethality table look-up server (the server). The ICD describes the interface to an existing implementation of the server (with its look-up table capability). The interface described in this report includes an area that provides for further expansion, allowing delivery of damage descriptions from near real-time physics-based vulnerability models (future dynamic calculation capability).

2. Scope

The HLA specification requires an object model template (OMT). This ICD describes and explains the server’s OMT object model components (7, 8). The server has an HLA interface. HLA object model components that are unique to the server are described in this ICD. Ancillary but required objects are only mentioned and referenced (all these are from the real-time platform reference federation object model (RPR FOM) (9)).

3. Simulation Object Model (SOM) Intent

The server’s SOM is designed to simply advertise its existence (via a small “service description” object class shown in table 1); the bulk of the SOM and work is then conducted via HLA interactions.

3.1 SOM Object Classes

The idea behind this general object class structure is that a future architecture would consist of various “services”. Thus, a “root service” should exist. “Service” fills this function. A LethalityServer as well as other services would stem from this node. MobilityServer and TerrainServer are not used by the LethalityServer. They are only conceptual examples of other services to illustrate this intended structure.

Table 1. Lethality server class structure

Class1	Class2
Service (PS)	LethalityServer (PS)
	MobilityServer (N)
	TerrainServer (N)

Table 2 names and explains the variables (attributes) within the service class structure.

Table 2. Object classes (server published)

Object Class	Attribute	Data Type	Attribute Description
Service (PS)	Type	Simulation Services Enum32	Name or type of a specific service. Intent: There may be several services of a particular class, each with various missions or degrees of fidelity. “Type” distinguishes one from another. (Type Example values: LethalityServer_Table Lookup (1) LethalityServer_DynamicCalculation (2)). See table 9 Enumerations.
Service. Lethality Server (PS)	VersionID	String	Revision control identifier. Intent: The server optionally accepts queries and delivers results based on a conventional protocol configured to a particular VersionID. Subscribing federates should warn if the revision ID (VersionID) is an unexpected value.

The other object class subscribed to is the BaseEntity.PhysicalEntity root from the RPR FOM (see table 3). The server monitors entity information here to know a target’s orientation and position at the time of munition detonations.

Table 3. Ancillary but required object classes (from RPR FOM)

Class1	Class2
BaseEntity [26] (S)	PhysicalEntity (S)

3.2 SOM Interaction Classes

The lethality server’s interaction class structure is shown in table 4. There is a “root service” interaction class for the same reason given for the “root service object class” (see table 1). That is, it is a logical point of entry for service-related interactions.

Table 4. Lethality server interaction class structure

Interaction1	Interaction2	Interaction3	Interaction4	Interaction5
Service (N)	Query (N)	Lethality (N)	TableLookUp (IS)	Parameters (IS)
				Result (IS)
	DynamicCalculation (N)		Parameters (N)	
			Result (N)	
	BroadcastInfo (N)	Lethality (N)	TableLookUp (IS)	Result (IS)
			DynamicCalculation (N)	Result (N)

The general concept of this interaction class structure is to embody the rudiments of a query-response mechanism. This query-response is portrayed in figure 1.




Figure 1. Query and response interaction.

In general, most of the time, the server is broadcasting damage resulting from some event. It does so by sending interaction data along the Service.BroadcastInfo.Lethality interaction hierarchy object structure, namely, InteractionRoot.Service.BroadcastInfo.Lethality.Table LookUp.Result. Subscribers to this interaction will receive a notification for every event that

could cause damage. Currently, the only event triggering a Lethality.TableLookUp.Result interaction is the RPR FOM “MunitionDetonation” interaction. This is portrayed in figure 2, and table 5 names and explains the variables (parameters) within the Service.BroadcastInfo.Lethality.TableLookUp.Result interaction object structure.




Figure 2. Resulting damage interaction.

3.3 Assumptions

- Receiving applications are expected to locally filter the messages based on their interest. This is because all results are broadcast. Only a tiny fraction of these will apply to any one entity (unless that entity is very unlucky).
- Affected entities are expected to logically “OR”¹ the resulting damage with their current damage state. This is because the currently implemented server does not use an entity’s current state when calculating damage. (This is because the underlying look-up tables generally assume damage on a “first hit” basis.) The result is that it is possible to receive a mobility-firepower kill (MF-Kill) followed by a second shot delivering a mobility kill (M-Kill). If the entity were to blindly follow the server, its overall state would improve after the second shot!

¹That is, entities are expected to combine a new damage state with their existing state.

Table 5. Lethality server interaction: “service.broadcastinfo.lethality.tablelookup” (server published)

Interaction Object	Parameter	Data Type	Parameter Description
Service. Broadcast Info. Lethality. Table LookUp	Event [Identifier] ID	Event Identifier Struct	An ID, generated by the issuing federate, used to associate related fire and detonation events. This ID identifies the detonation event whose results are about to be broadcast by the server. The “EventIdentifierStruct” data type is reused from the RPR FOM.
Service. Broadcast Info. Lethality. Table LookUp	DISevent Identifier ID	DISEvent Identifier Struct	The DIS event identifier record. This is the triple unsigned short used to identify events in the DIS (IEEE 1278) specification. It is here for DIS backward compatibility. If a querying federate is able to determine the DIS event (i.e., if it is monitoring raw DIS traffic as well as HLA traffic), then this field could be useful to a subscribing federate. However, there is no guarantee that the server too is able to monitor raw DIS traffic. If DIS traffic is monitored, the server will do its best to reconstruct the event ID; however, as different DIS-HLA gateways translate RPR FOM EventIDs to the “DIS Triple,” there can be no guaranteed linkage between the DISeventID and EventIdentifier ID
Service. Broadcast Info Lethality. Table LookUp. Result (PS)	Instan- taneous Damage	Damage Status Enum32	This is the instantaneous result of the subject damage event provided by the lethality server. It contains the results of the damage event (identified by TableLookUp.EventID) against the target (identified by TableLookup.Result.EntityID). Results are “instantaneous” because they are not cumulative (server contains no “memory” of the previous damage state) and they might not be repeatable. The simulating entity must logically “or” this damage result with its previous damage state.
	EntityID	Entity IdentifierS truct	The ID of the entity being analyzed for vulnerability to the subject damage event (this damage event is identified by TableLookup.EventIdentifierID). The “EntityIdentifierStruct” is reused from the RPR FOM.
	Entity Type	Entity Type Struct	This is the type identifier for the entity that is under threat. (Note: this information might be indirectly available via the EventIdentifierID parameter but is supplied here for convenience.)
	Threat Type	Entity Type Struct	The type of munition or damage device used to attack the threatened entity. (As with “EntityType,” this is provided for convenience and to avoid ambiguity.)
	Error	Boolean	If TRUE, then a valid look-up table or other data source could <i>not</i> be retrieved, and the results shown in the “InstantaneousDamage” parameter therefore have NO validity. If FALSE, then a data source was found and no other errors were detected. (See the parameter ErrorMessage.)
	Error Message	String	If an error occurred (parameter “Error” == TRUE) then this field may (or may not) supply a helpful error message in human readable text.
	Results Flag	LethalityV alue FlagEnum3 2	Tells more about the instantaneous result returned from a lethality query (or broadcast) interaction. By default, the server always returns a result from a query, but whenever ResultsFlag has any value other than “Success_NoError,” then that result is erroneous. This flag’s returned value can provide hints as to the error’s source. (See ResultsFlagText.)
	Results FlagText	String	Provides a very short text description of the results flag. (Basically, this is the text representation of the “ResultsFlag” enumerated LethalityValueFlagEnum32 value.)

The “Service.Query.Lethality.TableLookUp.Parameters” interaction class is where federates may query a lethality server for more specific information. A federate makes its query by issuing this interaction. The server responds by finding the results based on the passed interaction parameters and returns the results. Table 6 names and explains these parameters.

The Service.Query.Lethality.TableLookUp.Results is the area where results of the table look-up query are provided. Table 7 describes these returned parameters. The type of results returned depends on what was queried (See: Service.Query.Lethality.TableLookUp.Parameters, table 6).

Table 6. Lethality server interaction: “service.query.lethality.tablelookup.parameters” (server subscribed)

Interaction Object	Parameter	Data Type	Parameter Description
Service.Query.Lethality.TableLookUp	Event IdentifierID	Event Identifier Struct	An ID generated by the issuing federate, used to associate related fire and detonation events. This is the identifier that identifies a detonation event and is the subject of the lethality query.
	DISevent IdentifierID	DISEntity Identifier Struct	The DIS event identifier record. This is the triple unsigned short used to identify events in the DIS (IEEE 1278) specification. If a querying federate is able to determine the DIS event (i.e., if it is monitoring raw DIS traffic as well as HLA traffic), then this field could be filled. However, there is no guarantee that the server is able to monitor raw DIS traffic; thus, an error might be returned in the “Query.Lethality.Tablelookup.Result” interaction response.
Service.Query.Lethality.TableLookUp.Parameters	EntityID	Event Identifier Struct	The ID of the entity being analyzed for vulnerability to the subject damage event (this damage event is identified by TableLookup.EventIdentifierID).
	QueryID	string	An identifier provided by the querying federate. This identifier is returned with the query result in the TableLookup.Result.QueryID field.
	Special Query Parameters	Query Lethality Table Lookup Special Parameters Struct	This data structure is used to query the server for many types of information beyond the normal M, F, MF, K damage result. It can be used to view the initial conditions used by the server, display raw probability distributions (not just the outcome) or other information. If all the client wants is MFK results, then these parameters should be set to false.

Table 8 lists interactions defined in the RPR FOM to which the server subscribes. These are not explained, only referenced.

Enumerated data types and complex data types developed for the server are explained in tables 9 and 10, respectfully. Other enumerations are defined in the RPR FOM: DamageStatusEnum32, WarheadType16, FuseTypeEnum16, DetonationResultCodeEnum8, ForceIdentifierEnum8, MarkingEncodingEnum8, EventTypeEnum32.

Table 10 displays lethality server-defined complex data types. When executing a server query, querying federates set the Boolean “QueryLethalityTableLookupSpecialParametersStruct.

ProbabilityDistributionQuery” to TRUE if they wish to receive the five floating point numbers that represent the cumulative likelihood of only an M-Kill, only a firepower kill (F-Kill), an MF-Kill, catastrophic kill (K-Kill), and no damage. These values are “additive” (also known as thermometer redistribution). This means that within the set of five returned values, the first value is the probability of an M-Kill; the second floating point value returned is the sum of M-Kill + F-Kill; the third value is the sum of M-Kill + F-Kill + MF-Kill, and so forth.

Table 7. Lethality server interaction: “service.query.lethality.tablelookup.results” (server published)

Interaction Object	Parameter	Data Type	Description
Service.Query.Lethality.TableLookup.Results.	InstantaneousDamage	Damage StatusEnum 32	This is the instantaneous result of the subject damage event provided by the lethality server. It contains the results of the damage event (identified by TableLookUp.EventID) against the target (identified by TableLookup.EntityID). Results are “instantaneous” because they are not cumulative (the server does not consider the previous entity’s state when issuing damage from a new detonation), and the damage may not be repeatable. That is, repeated calls for the same detonation event can result in different outcomes (albeit drawn from the same distribution of outcomes).
	QueryID	string	An identifier returned by the server. This identifier was originally provided by the querying federate along with the query in the Service.Query.TableLookup.Parameters.QueryID field. The server returns the same value placed by the querying federate so that the federate may know the supplied result is in response to his query and not another’s.
	Error	Boolean	If TRUE, then a valid look-up table or other data source could <i>not</i> be retrieved and the results shown in the “InstantaneousDamage” parameter therefore have NO validity. If FALSE, then a data source was found and no other errors were detected. (See the parameter ErrorMessage.)
	Error Message	string	If an error occurred (parameter “Error” == TRUE), then this field may (or may not) supply a helpful error message in human readable text.
	ResultsFlag	Lethality ValueFlag Enum32	Tells more about the instantaneous result returned from a lethality query (or broadcast) interaction. By default, the server always returns a result from a query, but whenever ResultsFlag has any value other than “Success_NoError,” then that result is erroneous. This flag’s returned value can provide hints as to the error’s source. (See ResultsFlagText.)
	ResultsFlag Text	string	Provides a very short text description of the results flag. (Basically, this is the text representation of the “ResultsFlag” enumerated LethalityValueFlagEnum32 value; see table 9 Enumerations.)

Table 8. RPR FOM interactions (server subscribed)

Interaction Object	How Used	Reference
MunitionDetonation	1.) Server records internally. 2.) Triggers server to broadcast the resulting damage (BroadcastInfo.Lethality.TableLookUp.Result).	RPR FOM
WeaponFire	1) Server records. 2) Under certain circumstances, server may use some of this information to calculate MunitionDetonation damage (e.g., to resolve ambiguities in the range a munition was fired from).	RPR FOM

Table 9. Enumerations

Identifier	Enumerator	Representation
SimulationServicesEnum32	LethalityServer_TableLookup	1
	LethalityServer_DynamicCalculation	2
	TerrainServer_DataPointQueries	3
	SerialNumberGenerator	4
LethalityValueFlagEnum32	Success_NoError	0
	Error_Unknown	1
	Error_NoLookupTableFound	2
	Error_CorruptTable	3
	Error_MissingEnvironmentData	4

If a querying federate wishes to examine all initial conditions used to determine the vulnerability calculation, then “QueryLethalityTableLookupSpecialParametersStruct.InitialConditionsQuery” is set TRUE. The server then will return an ASCII (American Standard Code for Information Interchange) human readable list of its internal parameter values used for the subject detonation event. See “DISEventIdentifierID” in table 6 for an explanation of the DISEventIdentifierStruct. Complex data types defined for use by the server are shown in table 10.

Table 10. Complex data types

Complex Datatype	Field Name	Datatype	Cardinality
QueryLethalityTableLookupSpecialParametersStruct	ProbabilityDistributionQuery	boolean	1
	InitialConditionsQuery	boolean	1
QueryLethalityTableLookupSpecialResultStruct	ProbabilityDistributionMFK	float	5
	InitialConditions	string	1
DISEventIdentifierStruct	host	unsigned sho	1
	application	unsigned sho	1
	event_id	unsigned sho	1

Other server-used complex data types are defined in the RPR FOM: EventIdentifierStruct, Entity IdentifierStruct, EntityTypeStruct, RTIObjectIdStruct, RelativePositionStruct, VelocityVectorStruct, WorldLocationStruct, MarkingStruct, OrientationStruct, and AccelerationVectorStruct. AngularVelocityVectorStruct and ArticulatedParameterStruct are currently not used.

4. References

1. Sauerborn, G.C. *ARL Distributed Interactive Simulation (DIS) Lethality Communications Server, Volume II: User and Programmer's Manual*; ARL-TR-1775; U.S. Army Research Laboratory: Aberdeen Proving Ground, MD, February 1999.
2. Sauerborn, G.C. *Modifications of the Lethality Server for Initial RDEC Federation Integration*; ARL-MR-522; U.S. Army Research Laboratory: Aberdeen Proving Ground, MD, December 2001.
3. U.S. Army Aviation & Missile Research, Development, and Engineering Center (AMRDEC) *RDE Command First Application (1stApp) Final Report*, Redstone Arsenal, AL, 25 July 2003.
4. Sauerborn, G.C. *Ground Truth Lethality/Vulnerability Considerations in a Distributed Wide Area Environment (RDE Command 1stApp Case Study)*, Simulation Interoperability Standards Organization (SISO) Fall 2003 Simulation Interoperability Workshop (SIW), 03F-SIW-005, September 2003.
5. Weber, R.; Tackett, G.; Roose, K.; Larsen, K. *The Many Lessons from the RDE Command 1st Application - But did we learn anything?*, SISO, Fall 2003 SIW, 03F-SIW-005, September 2003.
6. Roose, K.; Tackett, G.; Heck, M.; Dykstra, P.; Birmingham, J.; Kile, T.; Valls, M. *The Architectural Design, Implementation and Observations of a Network, Built over the DREN, in Support of the Distributed HLA Simulation Federation of the RDE 1st Application*, SISO, Fall 2003 SIW, 03F-SIW-029, September 2003.
7. Sauerborn, G.C. *LServer_SOM_1_4.omd*; HLA 1.3 Object Model Template (OMT) file containing server-unique components, U.S. Army Research Laboratory: Aberdeen Proving Ground, MD, 11 June 2003. (This is useful when one is appending the server onto an RPR FOM-based federation OMT file.)
8. Sauerborn, G.C. *LServer_SOM_1_4_wRPRComponents.omd*; U.S. Army Research Laboratory: Aberdeen Proving Ground, MD, 11 June 2003 (unpublished OMT file that includes *only* those RPR FOM components that are used by the server; available from author).
9. Fischer, J.; Case, R.; Bertin, R., Eds. *Guidance, Rationale, and Interoperability Manual for the Real-time Platform Reference Federation Object Model (RPR FOM)*, Version 2.0D14v2, Simulation Interoperability Standards Organization, 11 March 2002.

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
* 1	ADMINISTRATOR DEFENSE TECHNICAL INFO CTR ATTN DTIC OCA 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218 *pdf file only
1	DIRECTOR US ARMY RSCH LABORATORY ATTN AMSRD ARL CI IS R REC MGMT 2800 POWDER MILL RD ADELPHI MD 20783-1197
1	DIRECTOR US ARMY RSCH LABORATORY ATTN AMSRD ARL CI OK TECH LIB 2800 POWDER MILL RD ADELPHI MD 20783-1197
1	DIRECTOR US ARMY RSCH LABORATORY ATTN AMSRD ARL D D SMITH 2800 POWDER MILL RD ADELPHI MD 20783-1197
1	DOD JOINT CHIEFS OF STAFF ATTN J39 CAPABILITIES DIV CAPT J M BROWNELL THE PENTAGON RM 2C865 WASHINGTON DC 20301
1	OFC OF THE DIR RSCH AND ENGRG ATTN R MENZ PENTAGON RM 3E1089 WASHINGTON DC 20301-3080
2	OFC OF THE SECY OF DEFNS ATTN ODDRE (R&AT) G SINGLEY ODDRE (R&AT) S GONTAREK THE PENTAGON WASHINGTON DC 20301-3080
1	AMCOM MRDEC ATTN AMSMI RD W C MCCORKLE REDSTONE ARSENAL AL 35898-5240
1	CECOM SP & TERRESTRIAL COM DIV ATTN AMSEL RD ST MC M H SOICHER FT MONMOUTH NJ 07703-5203
1	US ARMY INFO SYS ENGRG CMD ATTN ASQB OTD F JENIA FT HUACHUCA AZ 85613-5300

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	US ARMY NATICK RDEC ACTING TECHNICAL DIR ATTN SSCNC T P BRANDLER NATICK MA 01760-5002
1	US ARMY RSCH OFC 4300 S MIAMI BLVD RSCH TRIANGLE PK NC 27709
1	US ARMY STRICOM ATTN J STAHL 12350 RESEARCH PKWY ORLANDO FL 32826-3726
1	US ARMY TANK-AUTOMOTIVE & ARMAMENTS CMD ATTN AMSTA AR TD M FISETTE BLDG 1 PICATINNY ARSENAL NJ 07806-5000
1	US ARMY TANK-AUTOMOTIVE CMD RD&E CTR ATTN AMSTA TA J CHAPIN WARREN MI 48397-5000
1	US ARMY TRADOC BATTLE LAB INTEG & TECH DIR ATTN ATCD B J A KLEVECZ FT MONROE VA 23651-5850
1	NAV SURFACE WARFARE CTR ATTN CODE B07 J PENNELLA 17320 DAHLGREN RD BLDG 1470 RM 1101 DAHLGREN VA 22448-5100
1	DARPA 3701 N FAIRFAX DR ARLINGTON VA 22203-1714
1	HICKS & ASSOCIATES, INC. ATTN G SINGLEY III 1710 GOODRICH DR STE 1300 MCLEAN VA 22102
1	SPECIAL ASST TO THE WING CDR 50SW/CCX CAPT P H BERNSTEIN 300 O'MALLEY AVE STE 20 FALCON AFB CO 80912-3020
1	HQ AFWA/DNX 106 PEACEKEEPER DR STE 2N3 OFFUTT AFB NE 68113-4039

NO. OF
COPIES ORGANIZATION

1 CDR US ARMY AVIATION RDEC
AMES RSCH CTR
CHIEF CREW ST R7D
MS 243-4 DR N BUCHER
MOFFETT FIELD CA 94035

1 ITT INDUSTRIES
ATTN C WOODHOUSE
2560 HUNTINGTON AVE
ALEXANDRIA VA 22303

1 ITT INDUSTRIES
ATTN M J O'CONNOR
ADVNCED ENGINEERING & SCIENCES DIV
6767 OLD MADISON PIKE STE 160
HUNTSVILLE AL 35806

1 RAYTHEON SYSTEMS COMPANY
ATTN J D POWERS
6620 CHASE OAKS BLVD MS 8518
PLANO TX 75023

1 OPTOMETRICS INC
ATTN F G SMITH
3115 PROFESSIONAL DR
ANN ARBOR MI 48104-5131

1 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRD ARL SL EP G MAREZ
WSMR NM 88002

5 DIR US ARMY TRAC
ATTN ATRC WE L SOUTHARD
ATRAC WEC J AGUILAR
C DENNY D DURDA
P SHUGART
WSMR NM 88002

3 CDR TARDEC
ATTN AMSTA TR D M/S 207
FSCS R HALLE G SIMON
WARREN MI 48397-5000

3 CDR ARDEC
ATTN AMSTA AR FSS J CHU
D MILLER B DAVIS
PICATINNY ARSENAL NJ 07806-5000

1 DEF THREAT REDUCTION AGENCY
ATTN SWE W ZIMMERS
6801 TELEGRAPH RD
ALEXANDRIA VA 22310

NO. OF
COPIES ORGANIZATION

1 U.S. SBCCOM
NATICK SOLDIER CENTER
ATTN AMSSB RSS MA (N) D TUCKER
KANSAS STREET
NATICK MA 01760-5020

2 HQ OPERATIONAL TEST CTR
ATTN CSTE OTC MA S
CSTE OTC MA S J HAMILL
BLDG 91012
FT HOOD TX 76544-5068

1 SANDIA NATL LABORATORIES
ATTN M J MCDONALD
PO BOX 5800 MS-1004
ALBUQUERQUE NM 87185-1004

ABERDEEN PROVING GROUND

2 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRD ARL CI OK (TECH LIB)
BLDG 305 APG AA

8 DIR AMSAA
ATTN P DEITZ M BORROUGHS
B BRADLEY D HODGE
DON JOHNSON A WONG
K STEINER A DINSMORE
G DRAKE
BLDG 392

1 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRD ARL WM J SMITH
BLDG 4600

1 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRD ARL WM B A HORST
BLDG 4600

1 US ARMY RSCH LABORATORY
ATTN AMSRD ARL WM BE R SANDMEYER
BLDG 328

5 US ARMY RSCH LABORATORY
ATTN AMSRD ARL WM BE L BUTLER
J ANDERSON R BOWERS
C KENNEDY P TANENBAUM
BLDG 238

NO. OF
COPIES ORGANIZATION

- 5 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRD ARL WM BF G SAUERBORN
BLDG 309

- 2 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRD ARL CI CT G MOSS
M THOMAS
BLDG 321