



Optimal Design of a Two-Layered Elastic Strip Subjected to Transient Loading

by Ani P. Velo and George A. Gazonas

ARL-RP-93

May 2005

A reprint from the International Journal of Solids and Structures,
Vol. 40, pp. 6417–6428, 2003.

NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Aberdeen Proving Ground, MD 21005-5069

ARL-RP-93

May 2005

Optimal Design of a Two-Layered Elastic Strip Subjected to Transient Loading

Ani P. Velo
University of San Diego

George A. Gazonas
Weapons and Material Research Directorate, ARL

A reprint from the *International Journal of Solids and Structures*,
Vol. 40, pp. 6417–6428, 2003.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188		
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) May 2005		2. REPORT TYPE Reprint		3. DATES COVERED (From - To) July 2002–July 2003	
4. TITLE AND SUBTITLE Optimal Design of a Two-Layered Elastic Strip Subjected to Transient Loading			5a. CONTRACT NUMBER		
			5b. GRANT NUMBER		
			5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S) Ani P. Velo* and George A. Gazonas			5d. PROJECT NUMBER 62105AH84		
			5e. TASK NUMBER		
			5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRD-ARL-WM-MB Aberdeen Proving Ground, MD 21005-5069			8. PERFORMING ORGANIZATION REPORT NUMBER ARL-RP-93		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSOR/MONITOR'S ACRONYM(S)		
			11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES A reprint from the <i>International Journal of Solids and Structures</i> , Vol. 40, pp. 6417–6428, 2003. * Department of Mathematics and Computer Science, University of San Diego, CA 92110					
14. ABSTRACT Analytical solutions play a very important role in the validation of numerical codes. However, exact analytical solutions involving optimal design of transiently loaded multilayered structures are rare in the literature. In this report, we solve an optimal design problem involving wave propagation in a two-layered elastic strip subjected to transient loading. We obtain explicit formulas for the stress in each layer using the method of characteristics, and then use these results to identify the designs that provide the smallest stress amplitude. The derived analytical results are then successfully used to validate a previously developed, hybrid computational optimization software.					
15. SUBJECT TERMS wave propagation, layered media, transient structural optimization, functionally graded media					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UL	18. NUMBER OF PAGES 22	19a. NAME OF RESPONSIBLE PERSON George A. Gazonas
a. REPORT UNCLASSIFIED	b. ABSTRACT UNCLASSIFIED	c. THIS PAGE UNCLASSIFIED			19b. TELEPHONE NUMBER (Include area code) 410-306-0863



PERGAMON

International Journal of Solids and Structures 40 (2003) 6417–6428

INTERNATIONAL JOURNAL OF
**SOLIDS and
STRUCTURES**

www.elsevier.com/locate/ijsostr

Optimal design of a two-layered elastic strip subjected to transient loading

Ani P. Velo^a, George A. Gazonas^{b,*}

^a Department of Mathematics and Computer Science, University of San Diego, 5998 Alcalá Park, San Diego, CA 92110, USA

^b US Army Research Laboratory, Weapons and Materials Research Directorate, ATTN: AMSRL-WM-MB, Aberdeen Proving Ground, MD 21005-5069, USA

Received 19 December 2002; received in revised form 14 July 2003

Abstract

Analytical solutions play a very important role in the validation of numerical codes. However, exact analytical solutions involving optimal design of transiently loaded multilayered structures, are rare in the literature.

In this paper, we solve an optimal design problem involving wave propagation in a two-layered elastic strip subjected to transient loading. We obtain explicit formulas for the stress in each layer using the method of characteristics, and then use these results to identify the designs that provide the smallest stress amplitude. The derived analytical results are then successfully used to validate a previously developed, hybrid computational optimization software.

© 2003 Elsevier Ltd. All rights reserved.

Keywords: Wave propagation; Goupillaud-type layered media; Structural optimization; Analytical solutions; Validation of numerical codes

1. Prior work

The study of wave propagation in layered media is important in a number of diverse disciplines such as seismology, electromagnetics, optics, acoustics, et cetera. An exhaustive review of the literature on the subject is beyond the scope of this paper, and the reader is referred to the classic treatise by Brekhovskikh (1960) for a review of the mathematical framework and physical phenomena related to wave propagation in elastic and electromagnetic media. The different approaches to the design of layered media for optimal reflection/transmission characteristics, can be broadly classified into either frequency domain or time domain methods. Some relevant work in this area is included below. Using frequency domain methods, Hager et al. (2000) derive relations needed to minimize or maximize reflection in elastic coatings subjected to steady-state, band-limited, time-harmonic acoustic waves. Hager and Rostamian (1987) also investigate conditions necessary to minimize acoustic reflections from a wall with a viscoelastic coating. Wesolowski

* Corresponding author. Tel.: +1-410-306-0863; fax: +1-410-306-0759.

E-mail addresses: avelo@sandiego.edu (A.P. Velo), gazonas@arl.army.mil (G.A. Gazonas).

(1995) studies a problem for a two-layer interface sandwiched between homogeneous elastic layers subjected to time-harmonic waves. Gusev (2001, 2002) provides extremal relations for the optimal design of homogeneous and inhomogeneous layered structures subjected to time-harmonic acoustic waves. Abgaryan and Lyubashevskii (1984) develop relations for active suppression of time-harmonic waves in a structure containing a nondirectional sensor and radiator. Krasil'nikov (1983) uses the method of "slowly varying amplitudes" to find optimal designs for a multilayered interference absorber. Bao and Bonnetier (2001) consider an optimal design problem of a periodic structure subjected to time-harmonic, transverse magnetically polarized waves and establish the existence of the optimal designs for the class of problems investigated.

In contrast to the body of literature on time-harmonic wave propagation, there is much less published work on the optimization of layered media subjected to transient loading. Nygren et al. (1999) study the problem of maximizing the efficiency of elastic energy transmission through a layer of elastic junctions for application to percussive drilling. Konstanty and Santosa (1995) pose a transient optimal design problem for minimally reflective coatings in the time-domain, and solve the problem numerically using a BFGS updated secant method; their analysis is limited to problems with small interlayer impedance contrast. A number of other authors consider problems related to the propagation of stress waves in discretely layered or inhomogeneous media; however, these authors do not address the problem of optimization. For instance, Ali (1999) uses transmission line theory to obtain recurrence relation solutions for acoustic waves in a layered medium. Tenenbaum and Zindeluk (1992) develop exact algebraic expressions for the reflected wave in a semi-infinite layered homogeneous or inhomogeneous medium. Lee et al. (1975), provide some general expressions for the stress jump in both functionally graded and discretely layered media, and provide error estimates when a medium with continuous property variation is replaced by a medium consisting of a series of discrete homogeneous layers. Chiu and Erdogan (1999), and Scheidler and Gazonas (2002), solve several transient wave-propagation boundary-value problems for free-fixed and free-free boundary conditions in power-law and quadratic inhomogeneous one-dimensional media, using Laplace transform methods.

Anfinsen (1967) treats a boundary-value problem similar to our own, and finds optimal material properties which maximize/minimize the amplitude of the first transmitted stress wave along an elastic strip. Anfinsen develops difference equations and solves them using z -transform methods. In addition, Anfinsen determines asymptotic similarity relationships applicable for optimal two-layered designs. We corroborate Anfinsen's findings which show that increasing the impedance ratio of the layers tends to minimize the maximum stress on a design. Interestingly, despite the work of Anfinsen, our approach and results for the stress and optimal design of a two-layered elastic strip, appear to be entirely new. Furthermore, we use our analytical results to validate the hybrid DYNA3D/GLO optimization software (Gazonas and Randers-Pehrson, 2001), previously used to find optimal designs to a class of impact and penetration problems using constitutive behaviors representative of lightweight multilayered armors. Finally, we mention that Bruck (2000) develops a time history profile for the stress waves and discovers a time delay benefit when using functionally graded materials. In our work, we discover a similar benefit when using two-layered optimal designs other than the homogeneous. Such designs provide a time delay benefit when the peak values of stress are reached.

2. Analytical solutions for stress wave propagation and optimal design

We consider one-dimensional wave propagation in an isotropic elastic strip. The strip is assumed to be of finite length L , made of two layers of arbitrary lengths L_1 and L_2 , so that $L_1 + L_2 = L$. The layer interface is located at the fixed position $x = L_1$, where $0 < L_1 < L$. The left face of the strip is subjected to a stress loading p , while the right face is fixed (Fig. 1).




Fig. 1. Two-layered finite strip under transient load (physical coordinates).

The density and elastic modulus along the strip are denoted by the piece-wise constant functions $\rho(x)$ and $E(x)$, taking values ρ_1, ρ_2 , and E_1, E_2 , in each layer, respectively. In this work, we consider longitudinal elastic waves for a uniaxial strain state (Fig. 1), however our results are also valid for the case of uniaxial stress. Using the definitions of the wave speed $c = (E/\rho)^{1/2}$, and characteristic impedance $z = \rho c$, we relate to each layer the wave speed and characteristic impedance c_1, z_1 and c_2 and z_2 , respectively. The uniaxial strain elastic modulus E , is related to the Young’s modulus \bar{E} , through the expression $E = \bar{E}(1 - \nu)/[(1 + \nu)(1 - 2\nu)]$, where ν is Poisson’s ratio (Meyers, 1994).

Our design parameter α is chosen to represent the impedance ratio between layer 1 and layer 2: $\alpha = \frac{z_1}{z_2} > 0$. The transit time τ through the strip is given as

$$\tau = \frac{L_1}{c_1} + \frac{L_2}{c_2}.$$

Throughout this paper we assume a Goupillaud-type layered medium, which is a medium that ensures the same wave travel time through each layer, Claerbout (1976),

$$\frac{L_1}{c_1} = \frac{L_2}{c_2} = \frac{\tau}{2}. \tag{1}$$

In order to preserve the same wave travel time for both layers ($c_1/c_2 = L_1/L_2 = \mu$), the layer properties have to relate as: $\alpha = (\mu\rho_1)/\rho_2 = E_1/(\mu E_2)$. In the special case of two layers of equal length, $\mu = 1$ and the density and elastic modulus become proportional.

This problem can be easily converted to the case of two layers of equal length and wave speed of unity, by replacing the spatial variable x with the new variable $\xi = \int_0^x \frac{ds}{c(s)}$, and using condition (1). Here, $c \equiv c(s)$ is the piece-wise constant wave speed function, taking values c_1 and c_2 in each layer, respectively. As a result, the wave equation becomes:

$$z \frac{\partial^2 u}{\partial t^2} = \frac{\partial \left(z \frac{\partial u}{\partial \xi} \right)}{\partial \xi}, \tag{2}$$

where $z = z(\xi)$ represents the characteristic impedance given by the piece-wise constant function:

$$z(\xi) = \begin{cases} z_1, & \text{where } 0 < \xi < \frac{\tau}{2}, \\ z_2, & \text{where } \frac{\tau}{2} < \xi < \tau. \end{cases} \tag{3}$$

The wave speed now becomes the same (unity) in each layer ($c = c_1 = c_2 = 1$), while the design parameter $\alpha = \frac{z_1}{z_2} > 0$, as stated before.

Let $\sigma_\alpha(\xi, t)$ represent the value of the stress at position ξ , time t , and design parameter α . Our goal is to find a design that provides the smallest stress amplitude during the wave propagation along the strip. We formulate our optimal design problem as

$$(\mathbf{P}) \quad \inf_{\alpha > 0} \sup_{0 \leq \xi \leq \tau, 0 \leq t < +\infty} \sigma_\alpha(\xi, t),$$

subject to the initial/boundary-value problem,

$$\begin{cases} \frac{\partial^2 u}{\partial t^2} = \frac{\partial^2 u}{\partial \xi^2}, & \text{when } \xi \neq \frac{\tau}{2}, \\ \sigma(0, t) = z \frac{\partial u}{\partial \xi}(0, t) = p H(t), \quad u(\tau, t) = 0, \\ u(\xi, 0) = \frac{\partial u}{\partial t}(\xi, 0) = 0. \end{cases} \tag{4}$$

Here, $u(x, t)$ represents the displacement at (x, t) , and $H(t)$ represents the Heaviside function. As demonstrated later in the paper, solving problem **(P)**, becomes equivalent to solving the physical problem with layers of unequal lengths, because the only essential condition that influences the stress wave propagation along the strip, is the equal travel time through each layer. Therefore, from now on, any conclusions made for the case of two layers of equal length (Fig. 2), will apply to the general physical case of layers of unequal lengths (Fig. 1).

For the two-layered strip shown in Fig. 2, the propagation of the stress wave from layers 1 to 2, can be expressed by the following relations,

$$\sigma^- = \sigma^+ + [\sigma], \quad [\sigma]_T = \frac{2}{1 + \alpha} [\sigma]_I, \quad [\sigma]_R = \frac{1 - \alpha}{1 + \alpha} [\sigma]_I. \tag{5}$$

Here, σ^- and σ^+ represent the stress values behind and ahead of the discontinuity, while $[\sigma]$ represents the stress jump. The subscripts refer to I (incident), T (transmitted), and R (reflected) wave. The above relations, see Meyers (1994), involve the continuity conditions at the layer interface, and will be our main reference in calculating the stress values throughout this paper.

In the special case of a homogeneous design, when $\alpha = 1$, combining (5) with the method of characteristics, one can easily derive the time history profile for the stress. In the region ahead and behind the stress discontinuity propagating along the strip, the stress takes the following values, respectively,

$$\begin{cases} 0 \text{ and } p, & \text{during the time interval } (0, \tau), \\ p \text{ and } 2p, & \text{during the time intervals } ((2k - 1)\tau, 2k\tau) \text{ for } k = 1, 2, \dots, \infty, \\ 2p \text{ and } p, & \text{during the time intervals } (2k\tau, (2k + 1)\tau). \end{cases} \tag{6}$$

This implies that,

$$\max_{0 < \xi < \tau, 0 < t < +\infty} \sigma_1(\xi, t) = 2p, \tag{7}$$

where according to our notation, $\sigma_1(\xi, t)$ represents the stress at position ξ , time t , and design parameter $\alpha = 1$. From here, an upper bound for the optimization problem **(P)** follows,




Fig. 2. Two-layered finite strip under transient load (transformed coordinates).

$$\inf_{\alpha > 0} \sup_{0 \leq \xi \leq \tau, 0 \leq t < +\infty} \sigma_{\alpha}(\xi, t) \leq \max_{0 \leq \xi \leq \tau, 0 \leq t < +\infty} \sigma_1(\xi, t) = 2p. \tag{8}$$

Based on the results given later in this section, we prove that the reverse inequality in (8) holds, and conclude that the homogeneous design is an optimal design for problem (P). We also notice that no design with design parameter $\alpha < 1$, can be optimal, since for such designs the stress amplitude always exceeds the value $2p$. Indeed, following the first transmitted wave and using (5), it appears that in the region behind the stress discontinuity, the stress takes values,

$$\sigma(\xi, t) = \frac{2}{1 + \alpha} p > p, \quad \text{where } \frac{\tau}{2} < t < \tau \text{ and } \xi = t.$$

As the first transmitted wave reflects at the fixed boundary located at $\xi = \tau$, the stress doubles and reaches a value greater than $2p$. Summarizing the above observations we have,

$$\sup_{0 \leq \xi \leq \tau, 0 \leq t < +\infty} \sigma_{\alpha}(\xi, t) \geq 2p = \max_{0 \leq \xi \leq \tau, 0 \leq t < +\infty} \sigma_1(\xi, t), \quad \text{where } 0 < \alpha \leq 1. \tag{9}$$

In the rest of this paper, we investigate and obtain optimality results for two-layered designs with $\alpha > 1$. In Fig. 3a and b, are given the Lagrangian diagrams for the case of equal layer length under consideration, as well as for the general physical case of two layers of unequal lengths but equal travel time.

For a given $\alpha > 1$, after applying (5) and the method of characteristics, we find the following recurrence relation among the stress values $T_{\alpha,k}$,

$$\begin{cases} T_{\alpha,k} = \beta(\alpha) \cdot (T_{\alpha,k-1} - T_{\alpha,k-2}) + T_{\alpha,k-3}, & k = 4, 5, \dots, \infty, \\ T_{\alpha,1} = \frac{2}{(\alpha + 1)} p, \quad T_{\alpha,2} = \frac{8\alpha p}{(\alpha + 1)^2}, \quad T_{\alpha,3} = \frac{2(3\alpha - 1)^2 p}{(\alpha + 1)^3}, \end{cases} \tag{10}$$

where $\beta(\alpha) = \frac{3\alpha - 1}{\alpha + 1}$. The recurrence relation given in (10) is linear, homogeneous and with constant coefficients. Its corresponding characteristic equation,




Fig. 3. Lagrangian diagram of stress waves: (a) equal layer length, (b) unequal layer length.

$$T^k - \beta(\alpha) \cdot T^{k-1} + \beta(\alpha) \cdot T^{k-2} - T^{k-3} = 0,$$

has three distinct roots,

$$y_1 = 1, \quad y_2 = \frac{(\alpha - 1) + 2\sqrt{\alpha}\mathcal{I}}{\alpha + 1}, \quad \text{and} \quad y_3 = \frac{(\alpha - 1) - 2\sqrt{\alpha}\mathcal{I}}{\alpha + 1}, \tag{11}$$

where $\mathcal{I} = \sqrt{-1}$. The general solution is

$$T_{\alpha,k} = A_1 y_1^k + A_2 y_2^k + A_3 y_3^k \tag{12}$$

with coefficients A_1, A_2, A_3 determined from the boundary conditions given in (10),

$$A_1 = p, \quad A_2 = -\frac{p}{2}, \quad A_3 = -\frac{p}{2}. \tag{13}$$

Substituting (11) and (13) into (12), we obtain,

$$T_{\alpha,k} = p - \frac{p}{2} \left[\frac{(\alpha - 1) + 2\sqrt{\alpha}\mathcal{I}}{\alpha + 1} \right]^k - \frac{p}{2} \left[\frac{(\alpha - 1) - 2\sqrt{\alpha}\mathcal{I}}{\alpha + 1} \right]^k. \tag{14}$$

Further simplifications of (14), lead to the following expression for the term $T_{\alpha,k}$,

$$T_{\alpha,k} = p[1 - \cos(k\varphi(\alpha))], \tag{15}$$

where $\varphi(\alpha) = \arctan \frac{2\sqrt{\alpha}}{\alpha-1}$, and $\alpha > 1$. In fact, the following relations are equivalent,

$$\varphi = \arctan \frac{2\sqrt{\alpha}}{\alpha-1}, \quad \text{where } \alpha > 1 \tag{16}$$

and,

$$\alpha = \frac{1 + \cos \varphi}{1 - \cos \varphi}, \quad \text{where } 0 < \varphi < \frac{\pi}{2}. \tag{17}$$

From (15), one can derive the following bounds for the stress amplitude in layer 1,

$$0 \leq \sup_{0 < \zeta < \frac{\tau}{2}, 0 < t < +\infty} \sigma_\alpha(\zeta, t) \leq 2p, \quad \text{where } \alpha \geq 1. \tag{18}$$

These results indicate that for all designs with $\alpha \geq 1$, the stress amplitude in layer 1 never exceeds the value $2p$.

Similarly, using the continuity conditions at the layer interface and the method of characteristics, we derive that the new stress terms $S_{\alpha,k}$ satisfy the following relation,

$$\begin{cases} S_{\alpha,k} = -S_{\alpha,k-1} + 2T_{\alpha,k}, & k = 1, 2, \dots, \infty, \\ S_{\alpha,1} = 2T_{\alpha,1} = \frac{4}{(\alpha+1)}p, \end{cases} \tag{19}$$

or equivalently,

$$\begin{cases} S_{\alpha,k} = 2(-1)^k \sum_{i=1}^k (-1)^i T_{\alpha,i}, & k = 1, 2, \dots, \infty, \\ S_{\alpha,1} = 2T_{\alpha,1} = \frac{4}{(\alpha+1)}p. \end{cases} \tag{20}$$

Substituting the expression for $T_{\alpha,k}$ in (20), we further obtain,

$$S_{\alpha,k} = 2(-1)^k p \sum_{j=1}^k (-1)^j - 2(-1)^k p \sum_{j=1}^k (-1)^j \cos(j\varphi(\alpha)), \tag{21}$$

where as before $\varphi(\alpha) = \arctan(\frac{2\sqrt{\alpha}}{\alpha-1})$, and $\alpha > 1$. The calculation of each partial sum and further simplifications imply that the term $S_{\alpha,k}$ is given by the formula,

$$S_{\alpha,k} = p \left[1 - \frac{\cos((2k+1)\frac{\varphi(\alpha)}{2})}{\cos\frac{\varphi(\alpha)}{2}} \right]. \tag{22}$$

Due to the above expression for the terms $S_{\alpha,k}$, the stress amplitude in layer 2 will either reach or exceed the value $2p$, for any given design with $\alpha > 1$. A more detailed discussion is provided when the set K_α is introduced in (26). As a result we have,

$$\sup_{\frac{\tau}{2} < \zeta < \tau, 0 < t < +\infty} \sigma_\alpha(\zeta, t) \geq 2p, \quad \text{where } \alpha \geq 1. \tag{23}$$

Combining (18) and (23) we have that,

$$\sup_{0 \leq \zeta \leq \tau, 0 < t < +\infty} \sigma_\alpha(\zeta, t) \geq 2p, \quad \text{where } \alpha \geq 1. \tag{24}$$

Finally, combining (8), (9) and (24), we conclude that,

$$\inf_{\alpha > 0} \sup_{0 \leq \zeta \leq \tau, 0 \leq t < +\infty} \sigma_\alpha(\zeta, t) = \max_{0 \leq \zeta \leq \tau, 0 \leq t < +\infty} \sigma_1(\zeta, t) = 2p. \tag{25}$$

This clearly indicates that the homogeneous design with $\alpha = 1$, is an optimal design. Generally, a design with $\alpha > 1$ is optimal iff the stress values given by $S_{\alpha,k}$ for $k = 1, 2, \dots, \infty$, do not exceed $2p$.

Indeed, for any given $\alpha > 1$, we identify the set K_α as the set of all natural numbers $k = k(\alpha)$ such that $S_{\alpha,k} \geq 2p$. Based on the expression of the terms $S_{\alpha,k}$ given in (22), the condition $S_{\alpha,k} \geq 2p$, becomes equivalent to $\left[\frac{\cos((2k+1)\frac{\varphi(\alpha)}{2})}{\cos\frac{\varphi(\alpha)}{2}} \leq -1 \right]$, and furthermore to $\left[(2j+1)\pi - \frac{\varphi(\alpha)}{2} \leq (2k+1)\frac{\varphi(\alpha)}{2} \leq (2j+1)\pi + \frac{\varphi(\alpha)}{2} \right]$, where $j = 0, 1, 2, \dots, \infty$. As a result, we can describe the set K_α as

$$K_\alpha = \left\{ k : 2k + 1 \in \left[(2j + 1) \frac{2\pi}{\varphi(\alpha)} - 1, (2j + 1) \frac{2\pi}{\varphi(\alpha)} + 1 \right], j = 0, 1, 2, \dots, \infty \right\}. \tag{26}$$

For any given $\alpha > 1$, K_α is countably infinite because there is always at least one odd number of the form $2k + 1$, in an interval of two-unit length such as $[(2j + 1) \frac{2\pi}{\varphi(\alpha)} - 1, (2j + 1) \frac{2\pi}{\varphi(\alpha)} + 1]$ for $j = 0, 1, 2, \dots, \infty$. This proves that the terms $S_{\alpha,k}$, and therefore the stress amplitude, will reach or exceed the value $2p$ for some value of k , for every $\alpha > 1$. From here it follows that a design is optimal iff $S_{\alpha,k} = 2p$ for all $k \in K(\alpha)$. This is equivalent to the fact that $[2k + 1 = (2j + 1) \frac{2\pi}{\varphi(\alpha)} \pm 1]$ for $j = 0, 1, 2, \dots, \infty$, which combined with (16), (17) and (25), leads to the following necessary and sufficient condition for the optimal values of the design parameter α ,

$$\alpha_n = \frac{1 + \cos(\varphi_n)}{1 - \cos(\varphi_n)}, \quad \text{where } 0 < \varphi_n = \frac{\pi}{n} \leq \frac{\pi}{2} \text{ and } n = 2, 3, \dots, \infty. \tag{27}$$

Substituting these optimal values into the stress formulas $T_{\alpha,k}$ and $S_{\alpha,k}$, we find that these periodic functions have a time-period of $2n$, where the stress reaches its first peak of $2p$ at the n th time interval. These results, applied to the time history profiles involving the analytical solutions (15) and (22), match with the graphical output given in Figs. 4a and b and 5a and b, included in the next page. The normalized values for stress and time used in Figs. 4a and b and 5a and b, are calculated as, $\sigma^* = \frac{\sigma}{p}$, and $\mathcal{T} = \frac{t}{\tau}$.

Here p, τ are the initially given constants representing the stress loading, and the transit time through the elastic strip. We also notice that from (5), the stress jump at the optimal designs with parameter α_n takes values $[\sigma]_T = (1 - \cos(\frac{\pi}{n}))[\sigma]_I$, and $[\sigma]_R = -\cos(\frac{\pi}{n})[\sigma]_I$. In general, for the designs with parameter,

$$\alpha_{j,n} = \frac{1 + \cos \varphi_{j,n}}{1 - \cos \varphi_{j,n}}, \quad \text{where } 0 < \varphi_{j,n} = \frac{(2j + 1)\pi}{n} < \frac{\pi}{2}, \tag{28}$$

there are time intervals when the stress takes the value $2p$. Here j and n are natural numbers, chosen to satisfy the bounds for $\varphi_{j,n}$ given in (28).

The following examples, provide a means to better understand the structure of the K_α set and the conclusions made in this section.




Fig. 4. Optimal stress history when $\tau = 1$ and $\alpha = 3$: (a) layer 1: $\xi = 0.25$, (b) layer 2: $\xi = 0.75$.




Fig. 5. Optimal stress history when $\tau = 1$ and $\alpha = 32.163$: (a) layer 1: $\xi = 0.25$, (b) layer 2: $\xi = 0.75$.

Example 1. $\alpha = \frac{1+\cos(\pi/3)}{1-\cos(\pi/3)} = 3$. According to (27), such a design obtained for $n = 3$, is optimal. In this case $\varphi(\alpha) = \frac{\pi}{3}$ and (26) implies that,

$$K_\alpha = \{k : 2k + 1 \in [6(2j + 1) - 1, 6(2j + 1) + 1], j = 0, 1, 2, \dots, \infty\} \\ = \{6j + 2, 6j + 3, j = 0, 1, 2, \dots, \infty\}. \tag{29}$$

Based on the structure of K_α , the stress amplitude reaches its peaks when $S_{\alpha,6j+2} = 2p$, and $S_{\alpha,6j+3} = 2p$. As predicted for $n = 3$, the first peak is reached at the 3rd time interval with 6 units time-period. This can be verified by the graphical output given in Fig. 4b.

Example 2. $\alpha = \frac{1+\cos(5\pi/11)}{1-\cos(5\pi/11)}$. Here $\varphi(\alpha) = \frac{5}{11}\pi$ and from (26) we obtain,

$$K_\alpha = \left\{ k : 2k + 1 \in \left[\frac{22(2j + 1)}{5} - 1, \frac{22(2j + 1)}{5} + 1 \right], j = 0, 1, 2, \dots, \infty \right\}. \tag{30}$$

Although the design parameter α is not optimal, it satisfies the condition (28) for $j = 2$ and $n = 11$. One can easily check that although $S_2 > 2p$ and $S_6 > 2p$, there are indices such as $\{10, 11\} \subset K_\alpha$ for which $S_{10} = 2p$ and $S_{11} = 2p$, as predicted.

Example 3. $\alpha = \frac{1+\cos(\pi/\sqrt{6})}{1-\cos(\pi/\sqrt{6})}$. In this case we have that $\varphi(\alpha) = \pi/\sqrt{6}$ and from (26) we obtain,

$$K_\alpha = \{k : 2k + 1 \in [(4j + 2)\sqrt{6} - 1, (4j + 2)\sqrt{6} + 1], j = 0, 1, 2, \dots, \infty\}. \tag{31}$$

In this case, none of the conditions (27) or (28) is satisfied. This means that the design is not optimal and that all the terms $S_{\alpha,k}$ for $k \in K_\alpha$, will exceed the value $2p$ without ever reaching it, i.e. we expect that $S_{\alpha,k} > 2p, \forall k \in K_\alpha$.

In conclusion, in this work, we solve the problem of minimizing the stress amplitude for a two-layered elastic strip, with layers of equal wave travel time, and subjected to transient loading. Our results provide explicit formulas for the stress propagation and optimal designs in one-dimension, and apply for a two-layered elastic strip of unequal layer lengths.

3. Numerical results using DYNA3D/GLO optimization software

Since exact analytical solutions to optimal design problems involving transiently loaded multilayered structures are rare in the literature, analysts have relied on hybrid computational methods which link formal nonlinear parameter estimation algorithms with computational finite element methods for designing structures subjected to transient loadings. The results of the previous section provide useful benchmarks which can be used to validate these hybrid optimization design tools. Such a design tool was recently developed by Gazonas and Randers-Pehrson (2001), by coupling the global-local optimization software package known as GLO (Murphy, 1999) with the three-dimensional transient structural dynamics finite element code known as DYNA3D (Hallquist and Whirley, 1989). The local optimization algorithm within GLO is based upon the nonlinear optimization program NLQPEB that was developed by Baker (1992) for optimization of shaped charge jets.

The optimization software was tested to see if it could find any of the optimal points given by the optimality condition (27). The boundary value problem illustrated in Fig. 2 was modeled using DYNA3D with 60 hexahedral finite elements through the thickness. The optimization strategy is based upon a global-local approach since the optimal points in layer 2 contain an infinite number of minima, four of which are illustrated in Fig. 6. The plots in Fig. 6 were determined using our analytical expressions for stress, $S_{\alpha,k}$ and $T_{\alpha,k}$, through parametric variation of α over the range 0–10, and k to a time range out to 50 units.

The global optimization uses a discrete scheme which simply subdivides the design parameter α into uniformly spaced regions from which the local scheme can begin searching for extrema. The local scheme seeks to minimize the maximum stress in layer 2 using a BFGS variable-metric, sequential-quadratic-programming algorithm (Dennis and Schnabel, 1983), with a modified Powell merit function (Powell, 1977). Since the number of optimal designs is infinite in nature, the search was limited, rather arbitrarily, to a region involving the first eight optimal design points. Table 1 shows that the hybrid DYNA3D/GLO optimization software successfully found all of the first eight optimal design points to a reasonable degree of accuracy. This result both validates the DYNA3D/GLO optimization software and corroborates the optimality condition obtained earlier.

An example of optimal layer design for a two-layered elastic strip of equal lengths, is a design made of tungsten and lead ($\alpha = 3$) or a design made of tungsten and nylon ($\alpha = 32.163$). The proportionality between the density and elastic modulus in both layers, provide a constant wave speed and therefore equal travel




Fig. 6. Maximum stress vs. α in a two-layered finite strip showing the first four optimal α points given by optimality condition (27).

Table 1
Comparison of analytical and DYNA3D/GLO derived α values

n	2	3	4	5	6	7	8	9
α (Eq. (27))	1	3	5.828	9.472	13.983	19.196	25.270	32.163
α (DYNA/GLO)	1	3	5.829	9.470	13.924	19.182	25.247	32.120

times. These examples appear in Figs. 4 and 5, where it can be seen that the stresses never exceed the value of $2p$, a fact that qualifies them to be optimal designs. One can also observe that the time of onset of the maximum stress in each layer increases with the design parameter α . This means that if a design that delays the time of occurrence of the maximum stress is sought, then the value of the optimal design parameter α_n given in (27) should be maximized (within practical bounds). Because of such good agreement between the analytical results obtained previously and DYNA3D solutions, these findings support the use of purely computational means to establish optimal designs for transient problems of this nature.

Several other problems with different boundary conditions were then investigated using the DYNA3D/GLO software, including a two-layered free–free system with Heaviside loading, and two-layered free–free and free–fixed systems with rectangular pulse loading $p(t) = p(H(t) - H(t - t_0))$. Interestingly, none of these boundary-value problems provided optimal solutions with behavior similar to the optimality condition (27). However, for the free–fixed problem subjected to the rectangular pulse loading, as the value of t_0 increased and the loading approached that of a Heaviside loading, the optimal points (27) were gradually recovered.

4. Summary

In this paper, we investigated stress wave propagation in a two-layered elastic strip subjected to free–fixed boundary conditions under a Heaviside stress loading. Explicit expressions for the stress in each layer were obtained, and the countably infinite set of optimal designs which provide the smallest stress amplitude was identified. A time delay benefit when using optimal designs other than the homogeneous, was discovered. The analytical expressions for the stress in each layer compared well with the stress history profile predicted when using computational finite element methods. In addition, the optimality condition (27) provided means to validate a method based upon DYNA3D/GLO optimization software.

The validation of such computational optimization algorithms against known exact optimal solutions enables us to consider a broader class of impact and penetration problems using more realistic constitutive behaviors applicable to multilayered armor.

Acknowledgements

This research effort was sponsored by the Army Research Laboratory, with the support of the National Research Council. The authors would also like to acknowledge Dr. Michael J. Scheidler at the US Army Research Laboratory and Professor Konstantin Lurie at Worcester Polytechnic Institute, for their assistance and very valuable discussions during the course of this work. Dr. Scheidler originally generated Fig. 6 based upon a specialization of results for waves in graded media (Scheidler and Gazonas, 2002).

References

- Agbaryan, V.V., Lyubashevskii, G.S., 1984. Optimal synthesis of a controlled system for the suppression of traveling sound waves in a one-dimensional structure. *Sov. Phys. Acoust.* 30, 171–173.
- Ali, M.G., 1999. Discrete time model of acoustic waves transmitted through layers. *J. Sound Vib.* 224, 349–357.
- Anfinsen, L.E., 1967. Optimum design of layered elastic stress wave attenuators. *Trans. ASME J. Appl. Mech.* 34, 751–755.
- Baker, E.L., 1992. Modeling optimization of shaped charge liner collapse and jet formation. Ph.D. dissertation, Department of Mechanical and Materials Engineering, Washington State University, 163 pp.
- Bao, G., Bonnetier, E., 2001. Optimal design of periodic diffractive structures. *Appl. Math. Optim.* 43, 103–116.
- Brekhovskikh, L.M., 1960. *Waves in Layered Media*. Academic Press, NY.
- Bruck, H.A., 2000. A one-dimensional model for designing functionally graded materials to manage stress waves. *Int. J. Solids Struct.* 37, 6383–6395.
- Chiu, T.C., Erdogan, F., 1999. One dimensional wave propagation in a functionally graded elastic medium. *J. Sound Vib.* 23, 453–487.
- Claerbout, J.F., 1976. *Fundamentals of Geophysical Data Processing, with Applications to Petroleum Prospecting*. McGraw-Hill Inc., p. 274.
- Dennis, J.E., Schnabel, R.E., 1983. *Numerical Methods for Unconstrained Optimization and Nonlinear Equations*. Prentice Hall, NJ.
- Gazonas, G.A., Randers-Pehrson, G., 2001. Computational design and optimization of lightweight armor. In: Chou, S.-C. (Ed.), *Sagamore Army Materials Research Conference Proceedings*, vol. 45.
- Gusev, E.L., 2001. Internal structural symmetry of optimal layered structures. *Acoust. Phys.* 47, 45–49.
- Gusev, E.L., 2002. Optimal synthesis of inhomogeneous layered structures. *Acoust. Phys.* 48, 279–283.
- Hager, W.H., Rostamian, R., 1987. Optimal coatings, bang-bang controls, and gradient techniques. *Opt. Control Appl. Meth.* 8, 1–20.
- Hager, W.H., Rostamian, R., Wang, D., 2000. The wave annihilation technique and the design of nonreflective coatings. *Siam J. Appl. Math.* 60, 1388–1424.
- Hallquist, J.O., Whirley, R.G., 1989. *DYNA3D user's manual-nonlinear dynamic analysis of structures in three dimensions*. Report UCID-19592, Revision 5, Lawrence Livermore National Laboratory.
- Konstanty, H., Santosa, F., 1995. Optimal designs of minimally reflective coatings. *Wave Motion* 21, 291–309.
- Krasil'nikov, M.V., 1983. Optimal energy absorption conditions in multilayered resonant systems. *Sov. Phys. Acoust.* 29, 370–372.
- Lee, E.H., Budiansky, B., Drucker, D.C., 1975. On the influence of variations of material properties on stress wave propagation through elastic solids. *Trans. ASME J. Appl. Mech.* 42, 417–421.
- Meyers, M.A., 1994. *Dynamic Behavior of Materials*. John Wiley and Sons, NY.
- Murphy, M.J., 1999. GLO—global local optimizer user's manual. Report UCRL-MA-133858, Energetic Materials Center, Lawrence Livermore National Laboratory.
- Nygren, T., Andersson, L.E., Lundberg, B., 1999. Optimization of elastic junctions with regard to transmission of wave energy. *Wave Motion* 29, 223–244.
- Powell, M.J.D., 1977. A fast algorithm for nonlinearly constrained optimization calculations. In: Dold, A., Eckman, B. (Eds.), *Numerical Analysis*. In: *Lecture Notes in Mathematics*, vol. 630. Springer Verlag, NY.
- Scheidler, M.J., Gazonas, G.A., 2002. Analytical and computational study of one-dimensional impact of graded elastic solids. In: Furnish, M.D., Thadani, N.N., Horie, Y. (Eds.), *Shock Compression of Condensed Matter—2001*. Melville, NY, pp. 689–692.
- Tenenbaum, R.A., Zindeluk, M., 1992. An exact solution for the one-dimensional elastic wave equation in layered media. *J. Acoust. Soc. Am.* 92, 3364–3370.
- Wesolowski, Z., 1995. Optimisation of the transition zone between two homogeneous elastic materials. *Acta Mech.* 108, 133–141.

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1 (PDF ONLY)	DEFENSE TECHNICAL INFORMATION CTR DTIC OCA 8725 JOHN J KINGMAN RD STE 0944 FORT BELVOIR VA 22060-6218
1	US ARMY RSRCH DEV & ENGRG CMD SYSTEMS OF SYSTEMS INTEGRATION AMSRD SS T 6000 6TH ST STE 100 FORT BELVOIR VA 22060-5608
1	INST FOR ADVNCD TCHNLGY THE UNIV OF TEXAS AT AUSTIN 3925 W BRAKER LN STE 400 AUSTIN TX 78759-5316
1	US MILITARY ACADEMY MATH SCI CTR EXCELLENCE MADN MATH THAYER HALL WEST POINT NY 10996-1786
1	DIRECTOR US ARMY RESEARCH LAB IMNE ALC IMS 2800 POWDER MILL RD ADELPHI MD 20783-1197
3	DIRECTOR US ARMY RESEARCH LAB AMSRD ARL CI OK TL 2800 POWDER MILL RD ADELPHI MD 20783-1197
3	DIRECTOR US ARMY RESEARCH LAB AMSRD ARL CS IS T 2800 POWDER MILL RD ADELPHI MD 20783-1197

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
	<u>ABERDEEN PROVING GROUND</u>
1	DIR USARL AMSRD ARL CI OK TP (BLDG 4600)

NO. OF
COPIES ORGANIZATION

1 CECOM
SP & TRRSTRL COMMCTN DIV
AMSEL RD ST MC M
H SOICHER
FT MONMOUTH NJ 07703-5203

1 PRIN DPTY FOR TCHNLGY HQ
US ARMY MATCOM
AMCDCGT
R PRICE
5001 EISENHOWER AVE
ALEXANDRIA VA 22333-0001

1 PRIN DPTY FOR ACQUSTN HQS
US ARMY MATCOM
AMCDCGA
D ADAMS
5001 EISENHOWER AVE
ALEXANDRIA VA 22333-0001

1 DPTY CG FOR RDE HQS
US ARMY MATCOM
AMCRD
5001 EISENHOWER AVE
ALEXANDRIA VA 22333-0001

1 ASST DPTY CG FOR RDE HQS
US ARMY MATCOM
AMCRD
COL S MANESS
5001 EISENHOWER AVE
ALEXANDRIA VA 22333-0001

3 AIR FORCE ARMAMENT LAB
AFATL DLJW
W COOK
D BELK
J FOSTER
EGLIN AFB FL 32542

1 DPTY ASSIST SCY FOR R & T
SARD TT
THE PENTAGON RM 3E479
WASHINGTON DC 20310-0103

3 DARPA
L CHRISTODOULOU
W COBLENZ
S WAX
3701 N FAIRFAX DR
ARLINGTON VA 22203-1714

NO. OF
COPIES ORGANIZATION

1 DIRECTOR
US ARMY RESEARCH LAB
AMSRL CS AL TA
2800 POWDER MILL ROAD
ADELPHI MD 20783-1145

3 DIRECTOR
US ARMY ARDEC
AMSTA AR FSA E
W P DUNN
J PEARSON
E BAKER
PICATINNY ARSENAL NJ
07806-5000

2 US ARMY TARDEC
AMSTRA TR R MS 263
K BISHNOI
D TEMPLETON
WARREN MI 48397-5000

4 COMMANDER
US ARMY BELVOIR RD&E CTR
STRBE N WESTLICH
STRBE NAN
S G BISHOP
J WILLIAMS
FORT BELVOIR VA 22060-5166

2 COMMANDER
US ARMY RESEARCH OFFICE
A RAJENDRAN
J LAVERY
PO BOX 12211
RESEARCH TRIANGLE PARK NC
27709-2211

1 NAVAL RESEARCH LAB
A E WILLIAMS
CODE 6684
4555 OVERLOOK AVE SW
WASHINGTON DC 20375

5 DIRECTOR
LANL
P MAUDLIN
R GRAY
W R THISELL
A ZUREK
F ADDESSIO
PO BOX 1663
LOS ALAMOS NM 87545

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
7	DIRECTOR SANDIA NATL LABS E S HERTEL JR MS 0819 W REINHART T VOGLER R BRANNON MS 0820 L CHHABILDAS MS 1811 M FURNISH MS 0821 M KIPP MS 0820 PO BOX 5800 ALBUQUERQUE NM 87185-0307	4	UNIV OF NEBRASKA DEPT OF ENGINEERING MECH D ALLEN F BOBARU Y DZENIS J TURNER LINCOLN NE 68588
3	DIRECTOR LLNL M J MURPHY W TAO L282 A HOLT L290 PO BOX 808 LIVERMORE CA 94550	3	JOHNS HOPKINS UNIV DEPT OF MECH ENGINEERING J MOLINARI K T RAMESH F ZHOU LATROBE 122 BALTIMORE MD 21218
3	CALTECH M ORTIZ MS 105 50 G RAVICHANDRAN T J AHRENS MS 252 21 1201 E CALIFORNIA BLVD PASADENA CA 91125	1	WORCESTER POLYTECHNIC INST MATHEMATICAL SCIENCES K LURIE WORCESTER MA 01609
2	ARMY HIGH PERFORMANCE COMPUTING RSRCH CTR T HOLMQUIST G JOHNSON 1200 WASHINGTON AVE S MINNEAPOLIS MN 55415	4	UNIV OF UTAH DEPT OF MATHEMATICS A CHERKAEV E CHERKAEV T FOLIAS G MILTON SALT LAKE CITY UT 84112
3	SOUTHWEST RESEARCH INSTITUTE C ANDERSON J WALKER K DANNEMANN PO DRAWER 28510 SAN ANTONIO TX 78284	1	PENN STATE UNIV DEPT OF ENGG SCI & MECHANICS F COSTANZO UNIV PARK PA 16802
1	LIVERMORE SOFTWARE TECH CORP J O HALLQUIST 2876 WAVERLY WAY LIVERMORE CA 94550	3	UNIVERSITY OF DELAWARE DEPT OF MECH ENGINEERING T BUCHANAN T W CHOU M SANTARE 126 SPENCER LABORATORY NEWARK DE 19716
1	TEXAS A&M UNIV J WALTON DEPT OF MATHEMATICS COLLEGE STATION TX 77843	1	UNIVERSITY OF DELAWARE CTR FOR COMPOSITE MATERIALS J GILLESPIE NEWARK DE 19716
		3	SRI INTERNATIONAL D CURRAN D SHOCKEY R KLOPP 333 RAVENSWOOD AVE MENLO PARK CA 94025

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
1	VIRGINIA POLYTECHNIC INST COLLEGE OF ENGINEERING R BATRA BLACKSBURG VA 24061-0219	1	WASHINGTON ST UNIVERSITY SCHOOL OF MECH AND MATERIAL ENGINEERING J L DING PULLMAN WA 99164-2920
1	COMPUTATIONAL MECHANICS CONSULTANTS J A ZUKAS P O BOX 11314 BALTIMORE MD 21239-0314	2	WASHINGTON ST UNIVERSITY INSTITUTE OF SHOCK PHYSICS Y M GUPTA J ASAY PULLMAN WA 99164-2814
1	KAMAN SCIENCES CORP D L JONES 2560 HUNTINGTON AVE STE 200 ALEXANDRIA VA 22303	1	ARIZONA STATE UNIVERSITY MECH AND AEROSPACE ENGINEERING D KRAVCINOVIC TEMPE AZ 85287-6106
6	INST OF ADVANCED TECH UNIVERSITY OF TX AUSTIN S BLESS H FAIR D LITTLEFIELD C PERSAD P SULLIVAN S SATAPATHY 3925 W BRAKER LN STE 400 AUSTIN TX 78759-5316	1	UNIVERSITY OF DAYTON RESEARCH INSTITUTE N S BRAR 300 COLLEGE PARK MS SPC 1911 DAYTON OH 45469
1	APPLIED RSCH ASSOCIATES D E GRADY 4300 SAN MATEO BLVD NE STE A220 ALBUQUERQUE NM 87110	5	DIR USARL K WILSON FRENCH DEA 1396 ADELPHI MD 20783-1197
1	INTERNATIONAL RESEARCH ASSOCIATES INC D L ORPHAL 4450 BLACK AVE PLEASANTON CA 94566	1	TEXAS A&M UNIV DEPT OF GEOPHYSICS T GANGI COLLEGE STATION TX 77843
1	THE DOW CHEMICAL CO CENTRAL RSRCH ENGINEERING LABORATORY M EL RAHEB BLDG 1776 MIDLAND MI 48640		
1	BOB SKAGGS CONSULTANT S R SKAGGS 79 COUNTY RD 117 S SANTA FE NM 87501		

NO. OF
COPIES ORGANIZATION

ABERDEEN PROVING GROUND

77 DIR USARL
AMSRD ARL WM
J SMITH
J MCCAULEY
T WRIGHT
AMSRD ARL WM B
T KOGLER
AMSRD ARL WM BA
D LYON
AMSRD ARL WM BC
J NEWILL
P PLOSTINS
AMSRD ARL WM BD
P CONROY
B FORCH
R LIEB
M LEADORE
R PESCE-RODRIGUEZ
B RICE
AMSRD ARL WM BF
S WILKERSON
AMSRD ARL WM EG
E SCHMIDT
AMSRD ARL WM M
B BURNS
J BEATTY
AMSRD ARL WM MA
R JENSEN
S MCKNIGHT
M VANLANDINGHAM
E WETZEL
AMSRD ARL WM MB
M BERMAN
T BOGETTI
W CHOWDHURY
W DE ROSSET
R DOWDING
W DRYSDALE
A FRYDMAN
D HOPKINS
L KECSKES
T H LI
M MINNICINO
B POWERS
J SOUTH
J TZENG
AMSRD ARL WM MC
R BOSSOLI
S CORNELISON
T JENSEN
M MAHER
W SPURGEON

NO. OF
COPIES ORGANIZATION

AMSRD ARL WM MD
E CHIN
B CHEESEMAN
B DOOLEY
D ECKEL
C FOUNTZOULAS
G GAZONAS
J LASALVIA
P PATEL
W ROY
S WOLF
C F YEN
AMSRD ARL WM RP
J BORNSTEIN
C SHOEMAKER
AMSRD ARL WM T
S SCHOENFELD
M ZOLTOSKI
AMSRD ARL WM TA
J RUNYEON
AMSRD ARL WM TB
P BAKER
J STARKENBERG
AMSRD ARL WM TC
R COATES
M FERREN-COKER
K KIMSEY
D SCHEFFLER
S SCHRAML
AMSRD ARL WM TD
T BJERKE
S SEGELETES
D CASEM
D DANDEKAR
K IYER
M GREENFIELD
J CLAYTON
H W MEYER
M RAFTENBERG
E RAPACKI
M SCHEIDLER
T WEERASOORIYA
AMSRD ARL WM TE
G THOMSON
J POWELL

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	DERA N J LYNCH WEAPONS SYSTEMS BUILDING A20 DRA FORT HALSTEAD SEVENOAKS KENT TN 147BP UNITED KINGDOM	1	CENTRE D ETUDES DE GRAMAT J Y TRANCHET 46500 GRAMAT FRANCE
1	ERNST MACH INTITUT H NAHAME ECKERSTRASSE 4 D 7800 FREIBURG 1 BR 791 4 GERMANY	1	UNIVERSITY OF MANCHESTER N K BOURNE PO BOX 88, SACKVILLE STREET MANCHESTER M60 1QD UNITED KINGDOM
1	FOA2 P LUNDBERG S 14725 TUMBA SWEDEN	1	BEN GURIAN UNIVERSITY OF NEGEV E ZERETSKY DEPT OF MECH ENG BEER-SHEVA ISRAEL 84105
1	PCS GROUP CAVENDISH LABORATORY W G PROUD MADINGLEY RD CAMBRIDGE UNITED KINGDOM	2	RUSSIAN ACADEMY OF SCIENCES INSTITUTE FOR HIGH ENERGY DENSITIES G I KANEL S V RAZORENOV IVTAN, IZHORSKAYA 13/19 MOSCOW 127412 RUSSIA
1	TECHNICAL UNIV OF CRETE G EXADAKTYLOS DEPT OF MINERAL RES ENGNG CHANIA CRETE GREECE	1	INST FUR MATERIALFORSCHUNG II C TSAKMAKIS POSTFACH 3640 FORSCHUNGSZENTRUM KARLSRUHE D 76021 KARLSRUHE GERMANY
1	MINISTERE DE LA DEFENSE DR G BRAULT DGA DSP STTC 4 RUE DE LA PORTE DISSY 75015 PARIS FRANCE	1	NATL TECH UNIV OF ATHENS DEPT OF ENG SCI I VARDOULAKIS ATHENS 15773 GREECE
1	SPART DIRECTION BP 19 DR E WARINGHAM 10 PLACE GEORGES CLEMENCEOUX 92211 SAINT CLOUD CEDEX FRANCE	1	UNIV OF PATRAS DEPT OF CIVIL ENGINEERING D BESKOS PATRAS 26500 GREECE
1	ROYAL MILITARY COLLEGE OF SCIENCE CRANFIELD UNIVERSITY J MILLETT SHRIVENHAM SWINDON SN6 8LA UNITED KINGDOM	1	ARISTOTLE UNIV OF THESSALONIKI DEPT OF MECH & MATLS E AIFANTIS THESSALONIKI 54006 GREECE